


The Formwork Experts.

Framed formwork Frami S Xlife

User Information

Instructions for assembly and use



98032-200-01

Contents

4	Introduction
4	Basic safety warnings
7	Services
8	Framed formwork Frami S Xlife
9	Areas of use
11	Wall formwork
12	Instructions for assembly and use
18	The Frami panel in detail
20	Permissible fresh-concrete pressure
21	System grid
23	Adaptability
24	Joining gangs
26	Form-tie system
29	Length adjustment using fillers
36	90 degree corners
42	Shaft formwork
46	Acute and obtuse-angled corners
48	Bulkhead formwork
52	Wall junctions
54	Inter-panel connections for increased tensile loads
56	Vertical stacking of panels
62	Plumbing accessories
68	Pouring-platforms with single brackets
70	Lifting by crane
72	Transporting, stacking and storing
79	Column formwork
80	Design of column formwork
84	Pouring platform with Frami bracket 60
85	Lifting by crane
86	Footing and grade beam formwork
87	Tying horizontal Xlife panels
90	Tying upright Xlife panels
93	Tying horizontal Xlife universal panels
94	Plumbing accessories
95	Frost walls
97	General remarks
97	Frami combined with . . .
98	Cleaning and care of your equipment
100	Product overview

Introduction

Basic safety warnings

User target groups

- This booklet is aimed at all persons who will be working with the Doka product or system that it describes. It contains information on the standard design for setting up this system, and on correct, compliant utilization of the system.
- All persons working with the product described herein must be familiar with the contents of this booklet and with all the safety instructions it contains.
- Persons who are incapable of reading and understanding this booklet, or who can do so only with difficulty, must be instructed and trained by the customer.
- The customer is to insure that the information materials provided by Doka (e.g. User Information booklets, Method Statements, Operating Instruction manuals, plans etc.) are up to date and available to all users, and that users have been made aware of them and have easy access to them at the usage location.
- In the relevant technical documentation and formwork utilization plans, Doka shows the workplace safety precautions that are necessary in order to use the Doka products safely in the usage situations shown.
In all cases, users must ensure compliance with the national applicable laws, standards and rules throughout the entire project and to take appropriate additional or alternative workplace safety precautions where necessary.

Hazard assessment

- The customer is responsible for drawing up, documenting, implementing and continually updating a hazard assessment at every job-site. This booklet serves as the basis for the site-specific hazard assessment, and for the instructions given to users on how to prepare and utilize the system. It does not substitute for these, however.

Remarks on this booklet

- This document can be used as general Instructions for Assembly and Use (Method Statement) or be incorporated into site-specific Instructions for Assembly and Use (Method Statement).
- **The graphics, animations and videos in this document or app sometimes depict partially assembled assemblies and may require additional safety equipment and/or measures to comply with safety regulations.**
The customer must ensure all applicable regulations are complied with, even if they are not shown or implied in the graphics, animations and videos provided.
- **Individual sections contain further safety instructions and/or special warnings as applicable.**

Planning

- Provide safe workplaces for those using the formwork (e.g. for when it is being erected/dismantled, modified or repositioned etc). It must be possible to get to and from these workplaces via safe access routes!
- **If you are considering any deviation from the details and instructions given in this booklet, or any application which goes beyond those described in the booklet, then revised static calculations must be produced for checking, as well as supplementary assembly instructions.**

Regulations; occupational health & safety

- All laws, Standards, industrial safety regulations and other safety rules applying to the application and utilization of our products in the country and/or region in which you are operating must be observed at all times.
- If a person or object falls against, or into, the side-guard component and/or any of its accessories, the component affected may only continue in use after it has been inspected and passed by an expert.

Rules applying during all phases of the assignment:

- The customer shall ensure that this product is erected and dismantled, repositioned and generally used for its intended purpose in accordance with the applicable laws, standards and rules, under the direction and supervision of suitably skilled persons. These persons' mental and physical capacity shall not in any way be impaired by alcohol, medicines or drugs.
- Doka products are technical working appliances which are intended for industrial / commercial use only, always in accordance with the respective Doka User Information booklets or other technical documentation authored by Doka.
- The stability and load-bearing capacity of all components and units must be ensured during all phases of the construction work!
- Do not step on or apply strain to cantilevers, closures, etc. until suitable measures to ensure their stability have been correctly implemented (e.g. by tie-backs).
- The functional / technical instructions, safety warnings and loading data shall all be strictly observed and complied with. Non-compliance can cause accidents and severe injury (risk of fatality) and serious damage to property.
- Sources of fire in the vicinity of the formwork are prohibited. Heaters are permissible only when used correctly and situated at a correspondingly safe distance from the formwork.
- Customer must give due consideration to any and all effects of the weather on the equipment and regards both its use and storage (e.g. slippery surfaces, risk of slipping, effects of the wind, etc.) and implement appropriate precautionary measures to secure the equipment and surrounding areas and to protect workers.
- All connections must be checked at regular intervals to ensure that they are secure and in full working order.
In particular threaded connections and wedged connections have to be checked and retightened as necessary in accordance with activity on the jobsite and especially after out-of-the-ordinary occurrences (e.g. after a storm).
- It is strictly prohibited to weld or heat Doka products, particularly parts for anchoring, suspension or connecting, and also cast parts, etc.
Welding radically changes the micro-structure of the materials of which these components are made. This leads to a drastic reduction in failure load, constituting a serious safety risk.
It is permissible to cut individual tie rods to length with metal cutting discs (introduction of heat at the end of the rod only), but it is important to ensure that

flying sparks do not heat and thus damage other tie rods.

Welding work can be done only on the articles expressly mentioned in the Doka documents as being suitable for work of this nature.

Assembly

- The equipment/system must be inspected by the customer before use, to ensure that it is in suitable condition. Steps must be taken to rule out the use of components that are damaged, deformed, or weakened due to wear, corrosion or rot (e.g. fungal decay).
- The use of our safety systems and formwork systems in combination with those of other manufacturers could be dangerous, risking injury to health and damage to property, and therefore requires separate checking.
- The equipment/system must be assembled and erected in accordance with the applicable laws, standards and rules by suitably skilled personnel of the customer's, having regard to any and all required safety inspections.
- It is not permitted to modify Doka products; any such modifications constitute a safety risk.

Erecting the formwork

- Doka products and systems must be set up in such a way that all loads acting upon them are safely transferred!

Pouring

- Do not exceed the permitted fresh-concrete pressures. Excessively high pouring rates lead to formwork overload, cause greater deflection and risk causing breakage.

Stripping the formwork

- Do not strip the formwork until the concrete has reached sufficient strength and the person in charge has given the order for the formwork to be stripped!
- When stripping the formwork, never use the crane to break concrete cohesion. Use suitable tools such as timber wedges, special pry-bars or system features such as Framax S bias-cut corners.
- When stripping the formwork, do not endanger the stability of any part of the structure, or of any scaffolding, platforms or formwork that is still in place!

Transporting, stacking and storing

- Observe all country-specific regulations applying to the handling of formwork and scaffolding. For system formwork the Doka slinging means stated in this booklet must be used – this is a mandatory requirement.

If the type of sling is not specified in this booklet, the customer must use slinging means that are suitable for the application envisaged and that comply with the regulations.

- When lifting, always make sure that the unit to be lifted and its individual parts can absorb the forces that occur.
- Remove loose parts or secure them so that they cannot slip out of position and drop.
- All components must be stored safely, following all the special Doka instructions given in the relevant sections of this document!

Maintenance

- Only original Doka components may be used as spare parts. Repairs may only be carried out by the manufacturer or authorized facilities.

Miscellaneous

The weights are averages on the basis of new material. Actual weights can vary due to material tolerances. Weights can also differ on account of dirtying, moisture absorption, etc.

We reserve the right to make alterations in the interests of technical progress.

Symbols

The following symbols are used in this document:



DANGER

This is a notifier drawing attention to an extremely dangerous situation in which non-compliance with this notifier will lead to death or severe, irreversible injury.



WARNING

This is a notifier drawing attention to a dangerous situation in which non-compliance with this notifier can lead to death or severe, irreversible injury.



CAUTION

This is a notifier drawing attention to a dangerous situation in which non-compliance with this notifier can lead to slight, reversible injury.



NOTE

This is a notifier drawing attention to a situation in which non-compliance with this notifier can lead to malfunctions or damage to property.



Instruction

Indicates that actions have to be performed by the user.



Visual inspection

Indicates that actions performed must be checked by means of a visual inspection.



Tip

Draws attention to a useful tip for best-practice usage.



Reference

Cross-references other documents.

Services

Support in every phase of the project

- Project success assured by products and services from a single source.
- Competent support from planning through to assembly right on site.

Project assistance from start to finish

Every project is unique and calls for individualized solutions. When it comes to the forming operations, the Doka team can help you with its consulting, planning and ancillary services in the field, enabling you to carry out your project effectively, safely and reliably. Doka assists you with individual consulting services and customized training courses.

Efficient planning for a safe project sequence

Efficient formwork solutions can be developed economically only if there is an understanding of project requirements and construction processes. This understanding is the basis of Doka engineering services.

Optimize construction workflows with Doka

Doka offers special tools that help you design transparent processes. This is the way to speed up pouring processes, optimize inventories and create more efficient formwork planning processes.

Custom formwork and on-site assembly

Doka complements its system formwork with customized formwork units. Specially trained personnel assemble load-bearing towers and formwork on site.


Just-in-time availability

Formwork availability is vital for on-time, on-budget realization of your project. The worldwide logistics network puts the necessary formwork quantities on site at the agreed time.

Rental and reconditioning service

The formwork material needed for any particular project can be rented from Doka's high-performing rental park. Doka Reconditioning cleans and overhauls client-owned equipment and Doka rental equipment.

High performance, in all stages of the project



upbeat construction digital services for higher productivity

From planning through to completion - with upbeat construction we'll be moving construction forward and upping the beat for more productive building with all our digital services. Our digital portfolio covers the entire construction process and is being extended all the time. To find out more about our specially developed solutions go to doka.com/upbeatconstruction.

Framed formwork Frami S Xlife

Frami Xlife is ideal for fast, cost-saving forming both with and without a crane.

Saves time, cuts labor costs

with its system logic, ease of cleaning and low form-tie ratio

Frami Xlife has several features that make it extremely cost-efficient:

- its Xlife sheet is easier and quicker to clean
- it has a low form-tie ratio, which cuts costs
- it is quicker to reposition, as there is a clearly defined grid for the gang-forms
- shorter forming-times, as the system minimizes any filler zones

High economy, maximum lifespan

due to the Xlife sheet and galvanized hollow-section steel frames

The high product quality


- lowers close-out and rehabilitation costs
- ensures that the formwork system will have a long service life

Simplifies planning and handling

as the system can be used in so many different ways

The ingenious Frami Xlife formwork system gives you


- huge flexibility, because you can combine panel heights from 3'-0" to 9'-0"
- an efficient way of forming shafts, when combined with the Framax bias cut corner I
- rapid formwork planning using the professional Tipos-Doka software
- cost savings from reduced commissioning quantities




98032-200-01

Areas of use


Wall formwork




Column formwork




Footing and grade beam formwork





Wall formwork



98032-354-01

- A** Frami panel (Page 18)
- B** Joining gangs (Page 24)
- C** Form-tie system (Page 26)
- D** Length adjustment (Page 29)
- E** 90 degree corners (Page 36)
- F** Acute and obtuse-angled corners (Page 46)
- G** Bulkhead formwork (Page 48)
- H** Vertical stacking of panels (Page 56)
- I** Plumbing accessories (Page 62)
- J** Pouring-platforms (Page 68)
- K** Lifting by crane (Page 70)


Instructions for assembly and use

Using Frami as a manhandled formwork

The sequence shown here is based on a straight wall. As a rule, formwork set-up should start in a corner, working outward.

Transporting / handling the panels

- For offloading panels from a truck, or lifting them on-site a stack at a time, use the Frami transport hook and the Doka 4-part chain 3.20m (see 'Transporting, stacking and storing').



Erecting the formwork

- Spray the plywood face with release agent (see 'Cleaning and care of your equipment').



WARNING

- The Frami panels must be securely braced in every phase of the construction work!
- Fix the first panel to the ground with a panel strut (see 'Plumbing accessories'). This stabilizes the panel so that it cannot fall over.
- Use the nail-holes to fasten the panels to the ground or sills.




CAUTION

Never use a sledge-hammer to plumb and align the panels!

This would damage the profiles of the panels.

- Use only proper plumbing tools (e.g. a special pry-bar) that cannot cause any damage.
- Continue lining up panels in this way, clamp them together (see 'Joining gangs') and attach panel struts.




The gang can now be exactly plumbed and aligned.


Erecting the opposing formwork

Once the reinforcement has been placed, the formwork can be closed.


- Spray the formwork sheet of the opposing formwork with release agent.
- Stand up the first panel of the opposing formwork.
- Insert the form-ties (see 'Form-tie system'). Now the opposing formwork is also secured against falling over.



- In the same way, continue lining up panels, clamping them together and fitting form-ties.



- Mount the pouring platform and attach end-of-platform sideguards where necessary (see 'Pouring-platforms with single brackets').



Pouring

Permitted pressure of the fresh concrete:

See the section headed 'Permissible fresh-concrete pressure'.

Observe the following **guidelines**:

- The section headed 'Pressure of fresh concrete on vertical formwork – DIN 18218' in the Calculation Guide 'Doka formwork engineering'
- ACI 301 - 'Specifications for Structural Concrete'
- ACI 309 - 'Guide for Consolidation of Concrete'
- ACI 347 - 'Guide to Formwork for Concrete'
- SP4 - 'Formwork for Concrete'
- CAN/CSA S269.3 - 'Concrete Formwork'



NOTICE

- Do not exceed the maximum permissible rate of placing.
- Pour the concrete.
- Make only moderate use of vibrators, carefully coordinating the times and locations of vibrator use.

Stripping the formwork



NOTICE


- Observe the stipulated stripping times.
- Remove the pouring platform.
- Beginning with the unbraced formwork side, take down the panels one-by-one - take out the form-ties and undo the connectors to the adjacent panel.
- Lift the panel away and clean concrete residue off the formwork sheet (see 'Cleaning and care of your equipment').

Using Frami as a crane-handled formwork

The sequence shown here is based on a straight wall. As a rule, formwork set-up should start in a corner, working outward.


Transporting / handling the panels

- For offloading panels from a truck, or lifting them on-site a stack at a time, use the Frami transport hook and the Doka 4-part chain 3.20m (see 'Transporting, stacking and storing').



Pre-assembly

- Pre-assemble gang-forms face-down on an assembly bench (see 'Joining gangs').
- Mount the pouring platform and attach end-of-platform sideguards where necessary (see 'Pouring-platforms with single brackets').
- With the gang-form still flat, mount panel struts to it (see 'Plumbing accessories').




Erecting the formwork

- Attach the crane suspension tackle to the Frami lifting hook (see the section headed 'Lifting by crane' and the Operating Instructions for the 'Frami lifting hook').

Max. lifting capacity:

- Spread angle β up to 30°:
1100 lbs (500 kg) / Frami lifting hook
Practical area of formwork that can be lifted using 2 lifting hooks: approx. 270 sq.ft. (25 m²)
- Spread angle β up to 7.5°:
1650 lbs (750 kg) / Frami lifting hook
Practical area of formwork that can be lifted using 2 lifting hooks: approx. 400 sq.ft. (37.5 m²)

Frami lifting hooks with the rated load-bearing capacity of max. 1100 lbs (500 kg) also comply with the requirements for a load bearing capacity of 1650 lbs (750 kg) at a spread angle $\beta \leq 7.5^\circ$.



$\beta \dots \text{max. } 30^\circ$

- Pick up the gang-form by crane.
- Spray the plywood face with release-agent (see 'Cleaning and care of your equipment').



WARNING

- Do not allow people to ride on the formwork or platform.



NOTICE

- Make sure the tag-lines are long enough to enable the holders to stay outside the danger zone at all times.
- Fly the gang-form to its new location.




**CAUTION**

Never use a sledge-hammer to plumb and align the panels!

This would damage the profiles of the panels.

- Use only proper plumbing tools (e.g. a special pry-bar) that cannot cause any damage.
- Fix the panel struts firmly to the ground (see 'Plumbing accessories').

- Continue lining up gangs in this way, and link them together (see the section headed 'Joining gangs').




The gang-form is now stable and can be plumbed and aligned exactly, with no need for the crane.

- Detach the gang-form from the crane.
- Use nail-holes to secure the panels to the ground or the plumbing board.

Erecting the opposing formwork

Once the reinforcement has been placed, the formwork can be closed.

- Spray the plywood face with release agent (see 'Cleaning and care of your equipment').
- Fly the opposing formwork by crane to its next location.



- Insert the form-ties (see 'Form-tie system').



Before disconnecting from the crane:

- If there are no panel struts on the opposing formwork, do not disconnect the gang from the crane until a large enough number of form-ties have been installed to keep it safely in an upright position.
- Detach the gang-form from the crane (wherever possible, operate the lifting hook from the opposite pouring platform).
- Continue lining up adjacent gang-forms in this way, and clamp them together (see 'Joining gangs').

Pouring

Permitted pressure of the fresh concrete:

See the section headed 'Permissible fresh-concrete pressure'.


Observe the following **guidelines**:

- The section headed 'Pressure of fresh concrete on vertical formwork – DIN 18218' in the Calculation Guide 'Doka formwork engineering'
- ACI 301 - 'Specifications for Structural Concrete'
- ACI 309 - 'Guide for Consolidation of Concrete'
- ACI 347 - 'Guide to Formwork for Concrete'
- SP4 - 'Formwork for Concrete'
- CAN/CSA S269.3 - 'Concrete Formwork'



NOTICE

- Do not exceed the maximum permissible rate of placing.
- Pour the concrete.
- Make only moderate use of vibrators, carefully coordinating the times and locations of vibrator use.




Stripping the formwork




NOTICE

- ▶ Observe the stipulated stripping times.
- ▶ Remove any loose items from the formwork and pouring platform, or secure them firmly.
- ▶ Attach the gang-form of the unbraced formwork side to the crane (wherever possible, operate the lifting hook from the opposite pouring platform).
- ▶ Take out the form-ties and undo the connectors to the adjacent panels.



Gang-forms with only one panel strut must not be 'parked' upright, but placed face-down.

- ▶ Clean residual concrete off the formwork sheet (see 'Cleaning and care of your equipment').
- ▶ Where the gang-form has panel struts and a pouring platform attached to it, first attach this gang-form to the crane, and only then detach the floor anchorages of the panel struts.



In order to speed up operations when repositioning by crane, most of the form-ties can be taken out in advance.

Warning!

However, there must be at least as many form-ties left in place as are needed to keep the gang safely in an upright position.



WARNING


The formwork tends to adhere to the concrete. When stripping the formwork, do not try to break concrete cohesion using the crane!

Risk of injury and damage to property due to crane overload.


- ▶ Use suitable tools such as timber wedges or a special pry-bar to detach the formwork from the concrete.
- ▶ Pick up the gang-form and fly it to its next location. If the gang-form is 'parked' in the upright prior to its next use, it must have sufficient stability (see 'Plumbing accessories').

The Frami panel in detail

High load-bearing capacity



Tie-hole




b ... Diameter 1 1/8" (28 mm)

A Form-tie protector

B Xlife sheet

- Xlife sheet protected around the tie-holes by integrated form-tie protectors




Clean concrete surfaces with the innovative Xlife sheet

The Xlife sheet consists of a **combination of a plywood core and plastic coating**.

This combination of materials ensures high numbers of repeat uses, with superb concrete results every time, and reduces the proneness to damage.

- High quality concrete finish
- Less touching-up needed
- Less cleaning work – the Xlife sheet can also be cleaned using a high-pressure washer

Dimensionally stable steel hollow-profile frame



a ... 3 1/2" (9.2 cm)

A Frame profile


B Continuous hardware slot for inter-panel connectors

C Formwork sheet

D Silicone sealing strip

- Dimensionally stable hollow profiles
- Hot-dip galvanized for long life
- Strong cross-profiles
- Edge faces are easy to clean - so panels always abut tightly
- All-round hardware slot for fastening clamps at any point required
- Edges of formwork sheet are protected by frame profile
- Cross boreholes for corner configurations and bulk-heads

Accessories are easy to fasten in the cross profile



- A Frami S Xlife panel
- B Frami wedge clamp
- C Frami universal waling


Nail-holes

- are integrated in the frame profile to make it easier to attach or nail the panel to the ground or sills
- the nail-holes are located all around the frame, so the panels can be arranged either vertically or horizontally

Safety handles

Note:

Do not get onto and climb up the formwork, or use the safety handles, until the panels have been properly braced.



- A Integral safety handle

- are used to tie off safety harnesses.



WARNING

Do not use the safety handles as slinging points for crane-handling!

Danger of formwork dropping from crane!



- Use only suitable load-carrying equipment and slinging points. See 'Lifting by crane' and 'Transporting, stacking and storing'.

Permissible fresh-concrete pressure

Vertically stacked formwork

Permitted pressure of fresh concrete, **vertically stacked formwork**:

$$\sigma_{hk} = 1000 \text{ psf (48 kN/m}^2\text{)}$$



Permissible fresh-concrete pressure as a function of the maximum panel width

	Max. width of panel	Permitted fresh-concrete pressure $\sigma_{hk, \max}$		
		1000 psf (48 kN/m ²)	1200 psf (58 kN/m ²)	1500 psf (72 kN/m ²)
Frami S Xlife panel (all panel heights)	8'-0"	✓		
	3'-0"	✓		
	2'-6"	✓	✓	
	2'-0"	✓	✓	✓
	1'-6"	✓	✓	✓
	1'-0"	✓	✓	✓
	6"	✓	✓	✓
Frami S Xlife universal panel (all panel heights)	3'-0"	✓		

This means that for higher pour-pressures of up to **1200 psf (58 kN/m²)**, it is only allowed to use panels of 2'-6", 2'-0", 1'-6", 1'-0" and 6" in width.

For higher pour-pressures of up to **1500 psf (72 kN/m²)**, it is only allowed to use panels of 2'-0", 1'-6", 1'-0" and 6" in width.


Note:

All other Frami accessories can be subjected to increased pour pressures of up to 1500 psf (72 kN/m²) (only when the approved Frami S panels are used as per the above table).

Not vertically stacked formwork

Frami S Xlife panels of height 9'-0" are hydrostatically loadable up to a pour height of 9'-0" (2.74 m).



$$\sigma_{hk, \max, \text{hydr}} = 1430 \text{ psf (68.5 kN/m}^2\text{)}$$





System grid

Frami S Xlife panels

Heights of panels




Dimensions in inches




Dimensions in cm

For pour heights of up to 9'-0" (2.74 m) only **2 form ties** are needed in the vertical.


Widths of panels



Panel 8'-0"x9'-0"



Dimensions in inches



Dimensions in cm

Consult your Doka technician for more information on the use of this panel.

For pour heights of up to 9'-0" (2.74 m) only **2 form ties** are needed in the vertical.


Frami Xlife universal panels

The **3'-0" wide** panels are also available as **Universal panels** with heights of 2'-0", 3'-0", 4'-0", 6'-0" and 9'-0".


The special hole pattern makes these panels particularly suitable for efficient forming of:

- corners
- wall junctions
- bulkheads
- columns


Panel width



Heights of panels



Dimensions in inch




Dimensions in cm

Adaptability

Possible combinations


The perfect panel size-grid gives you innumerable possible combinations, in both width and height. You can use the panels either **vertical** or **horizontal**, and the **6" (15 cm) increment-grid** gives you optimum adaptability of the formwork to the dimensions of the structure, at all times.



Schematic representation

Infinite height offset


The continuous hardware slot around the inside of the Frami panels enables the clamps to be fastened anywhere on the frame. This allows any adjacent panels to be **staggered to any height required**, i.e. without being confined to any fixed grid. This means that the formwork can easily be accommodated to e.g. steps, slopes and uneven ground, with no extra work.



Schematic representation


Continue forming with job-built fillers

The framed formwork Frami also gives you easy connections when you need to 'make up' with job-built timber formwork. The Frami universal waling and filler angle make it easy for you to join the panels to dimensional lumber and plywood.



- A Frami universal waling
- B Frami wedge clamp
- C Frami S filler angle 3/4"
- D Frami clip
- E Dimensional lumber
- F Formwork sheeting
- G Frami S Xlife panel

Joining gangs



Attributes of the gang connectors:

- provide self-aligning, crane-handling-safe connections between the gangs
- no losable small parts
- dirt-resistant and hard-wearing for site use
- easy to fix, with a formwork hammer



NOTICE

- Use a formwork hammer weighing max. 32 oz. (800 g).
- Do not oil or grease wedge-clamped joints.

Upright panels:

Panel height	Number of clamps
3'-0"	2
4'-0"	2
6'-0"	2
9'-0"	3

Horizontal panels:

Panel width	Number of clamps
6"	1
1'-0"	1
1'-6"	1
2'-0"	2
2'-6"	2
3'-0"	2


Note:

- For details regarding extra inter-panel connections for outside corners and bulkheads (for increased tensile loads): see 'Inter-panel connections for increased tensile loads'.

- For details on the position of the connector components needed in vertical stacking, see 'Vertical stacking of panels'.

Simple inter-panel connections

with the Frami clamp





Frami clamp:

Permitted tensile force: 2.245 kip (10.0 kN)

Permitted shear force: 1.12 kip (5.0 kN)


Permitted moment: 0.15 kip-ft (0.20 kNm)

The continuous hardware slot running around the inside of the frame profile means that panels can be fastened together anywhere on the frame. This allows adjacent panels to be staggered in height, infinitely.



Self-aligning inter-panel connections and fillers


with the Frami adjustable clamp




Frami adjustable clamp:

Permitted tensile force: 1.685 kip (7.5 kN)

Filler gaps can be closed easily and economically with Frami S steel fillers. With the Frami adjustable clamp, the panels are joined so that they are resistant to tensile forces, and are aligned at the same time. The adjustable clamp is placed directly over the cross profile.




a ... max. 6" (15 cm)




In cases where the Frami adjustable clamp would collide with steel fillers, universal walings, etc., it must be located next to the cross profile (instead of directly over it).


Formwork height: 9'-0" (2.74 m)




Formwork height: 6'-0" (1.82 m)



Formwork height: 4'-0" (1.22 m)




Formwork height: 3'-0" (0.91 m)



Form-tie system

Tying the Frami panels



Tying Frami S Xlife panels 9'-0":


Up to a **pour height of 9'-0" (2.74 m)** (with no vertically stacked panels), **only 2 form-ties** are required in the vertical.

Apart from this, the basic rule here is:

Place a form-tie in every form tie hole within a panel that is not covered by a tie washer (e.g. at a panel joint, only tie one of the two adjoining panels).

Always tie in the bigger (wider) of the two panels.

For exceptions, see 'Length adjustment using fillers' and 'Vertical stacking of panels'.



WARNING

Sensitive rod steel!

- Never weld or heat tie-rods.
- Tie rods that are damaged or have been weakened by corrosion or wear must be withdrawn from use.

Note:

Close off unneeded tie-holes with Frami S frame-hole plugs.


Note:

Doka also offers economical solutions for creating watertight wall-ties.



For more information, see the User Information booklet 'Doka form-ties for special requirements'.

Taper-tie system 3/4" to 1"



A Super-plate 15.0

B Taper tie 3/4" to 1" & 5/8" [15.0] ends

For forming wall thicknesses in the 6" to 30" (15.2 to 76.2 cm) range, there are 4 different types of taper tie:

Wall thickness:		Form-tie length
6" to 12"	(15.2 to 30.5 cm)	32"
12" to 18"	(30.5 to 45.7 cm)	38"
18" to 24"	(45.7 to 61.0 cm)	44"
24" to 30"	(61.0 to 76.2 cm)	52"


Note:

Always loosen the Super-plate on the thinner end of the taper tie first.

Taper tie 3/4" to 1" & 5/8" [15.0] ends:

Permitted capacity allowing a 2 : 1 factor of safety against failure: 18,000 lbs (80 kN)

She-bolt system 15.0 (5/8")




- A** Frami S she-bolt 15.0mm x 16"
(or Frami S she-bolt 15.0mm x 24" for special applications)
- B** Super-plate 15.0
- C** Euro rod 5/8" or Tie-rod 15.0mm
Length= Wall thickness – 4" (10 cm)

▪ She-bolt system 15.0 (5/8")

Permitted capacity allowing a 2 : 1 factor of safety against failure:
18000 lbs (80 kN)

Tie-rod system 15.0 (5/8")

The Form-tie system 15.0 makes it possible to tie panels in narrow or confined spaces. For areas of application, see 'Acute and obtuse-angled corners'.



- A** Super-plate 15.0
- B** Tie-rod 15.0mm
- C** Plastic tube 22mm
- D** Universal cone 22mm

Note:

The Plastic tubes 22mm left behind in the concrete are sealed off with **Plugs 22mm**.



Spanner for tie-rod 15.0/20.0


For turning and holding the tie-rods.




Tie-rod 15.0mm:

Permitted capacity, allowing a 2 : 1 factor of safety:
22,000 lbs (98 kN)

Sloping ties on height-mismatched panels

Thanks to the special shape of the Super-plate, the panels can be inclined on one or both sides, and/or height-mismatched.







Inclined on one side	Inclined on both sides	Height mismatch
max. 4°	max. 2 x 4°	Form-tie system 15.0: max. 1/2" per 6" wall thickness (1.2 cm per 15 cm) Taper tie 3/4" to 1" & 5/8" [15.0] ends: max. 1/4" per 6" wall thickness (0.6 cm per 15 cm)
		
98032-240-01	98032-241-01	98032-242-01

Note:

Secure inclined panels against uplift.


Form-tie situations



Length adjustment using fillers

with steel fillers and adjustable clamps

By combining the steel filler widths of 1", 1 1/2", and 2" in various ways, the closures can be made in 1/2" (13 mm) increments.





- A** Frami S steel filler 2" (with through-tie facility)
- B** Frami S steel filler 1 1/2"
- C** Frami S steel filler 1"
- D** Frami clip
- E** Frami S Xlife panel



In order to get a firm link between the filler and the panels, fix the steel fillers in place with Frami clips (**D**) .

Note:

Form ties can be placed through the 2" (5 cm) wide Frami S steel filler. The steel filler through which the tie is being placed must be fitted in a central position.

Up to 3" (7.6 cm) filler	Up to 6" (15 cm) filler
Place form ties in panel, with universal waling	Place form ties in filler, with universal waling
	


We also offer several other solutions for filler widths of 2" (5 cm), 3" (7.6 cm), and 6" (15 cm).

Note:

Close off unneeded tie-holes with **Frami plugs**.

Frami universal waling

Permitted moment: 0.96 kip-ft (1.3 kNm)




Note:


Where form ties are inserted through the panel frames, the Universal waling must rest on the cross profile.

Tying through the panel

(A) Universal waling in the horizontal (over the cross profile)





(B) Universal waling at an angle (so that it rests on the cross profile)




Tying through the filler

Universal waling in the horizontal



Filler width 1" (2.5 cm)


Place form-ties in panel, with universal waling



1 Frami S steel filler 1"

Filler width 2" (5.1 cm)


Place form-ties in filler, without universal waling.



1 Frami S steel filler 2"

Filler width 1 1/2" (3.8 cm)


Place form-ties in panel, with universal waling



1 Frami S steel filler 1 1/2"

Filler width 2 1/2" (6.4 cm)


Place form-ties in panel, with universal waling



1 Frami S steel filler 1"
1 Frami S steel filler 1 1/2"

Filler width 2" (5.1 cm)


Place form-ties in panel, with universal waling



2 Frami S steel fillers 1"

Filler width 3" (7.6 cm)


Place form-ties in panel, with universal waling



2 Frami S steel fillers 1 1/2"

Filler width 3" (7.6 cm)


Place form-ties in filler, with universal waling



1 Frami S steel filler 1"
1 Frami S steel filler 2"

Filler width 4 1/2" (11.4 cm)


Place form-ties in filler, with universal waling



1 Frami S steel filler 1"
1 Frami S steel filler 1 1/2"
1 Frami S steel filler 2"

Filler width 3 1/2" (8.9 cm)


Place form-ties in filler, with universal waling



1 Frami S steel filler 1 1/2"
1 Frami S steel filler 2"

Filler width 5" (12.7 cm)


Place form-ties in filler, with universal waling



2 Frami S steel fillers 1 1/2"
1 Frami S steel filler 2"

Filler width 4" (10.2 cm)


Place form-ties in filler, with universal waling



2 Frami S steel fillers 2"

Filler width 5 1/2" (14 cm)


Place form-ties in filler, with universal waling



1 Frami S steel filler 1 1/2"
2 Frami S steel fillers 2"

Filler width: 6" (15.2 cm)


Place form-ties in filler, with universal waling



3 Frami S steel fillers 2"

- A** Frami adjustable clamp
- B** Frami S steel filler
- C** Frami universal waling
- D** Form-tye

A combination of three Frami S steel fillers 2" is used if it is necessary to tie through a 6" (15 cm) filler.





- a ... 14" (35.5 cm)
- b ... 12" (30.5 cm)

- A** Frami S Xlife inside corner
- B** Frami S outside corner
- C** Frami clamp
- D** Frami adjustable clamp
- E** Frami universal waling
- F** Frami S steel filler
- G** Frami S Xlife panel 2'-0"
- H** Frami S Xlife panel 2'-0"

with Frami S Xlife panel 6"

Filler width: 6" (15.2 cm)



- A** Frami clamp
- B** Frami S Xlife panel 6"x9'-0"
- C** Tie-rod

using filler angles and plywood

Required numbers of Frami clips:



Frami S filler angle 3/4"	N° of units
3'-0"	2
4'-0"	2
6'-0"	3
9'-0"	4



NOTICE

Where tensile loads occur (on corners and bulkheads), suitable tension anchoring must be provided.



Filler width: 4" - 10" (10.2 - 25.4 cm)



a ... 4" to 10" (10.2 to 25.4 cm)

- A** Frami S filler angle
- B** Frami clip
- C** Plywood 3/4"
- E** Frami universal waling 1.25 m
- F** Frami wedge clamp
- G** Form-tie

Filler width: > 10" - 20" (> 25.4 - 50.8 cm)



a ... > 10" to 20" (> 25.4 to 50.8 cm)

- A** Frami S filler angle
- B** Frami clip
- C** Plywood 3/4"
- D** Dimensional lumber 2 3/4"
- E** Frami universal waling 0.70m and 1.25m
- F** Frami wedge clamp
- G** Form-tie



Possible ways of attaching Universal walings:

For accessories with an **overall height of 2" (5 cm)** (Frami universal waling **(E)**):

- Frami wedge clamps **(F)**

For accessories with an **overall height of 2" to 4" (5 cm to 10 cm)** (e.g. Framax S universal waling **(H)**):


- Frami universal fixing bolt **(I)** + Super-plate **(J)**




Vertical stacking with fillers

Due to the space constraints encountered here, the Universal waling is generally positioned on the panel joint at an angle.



Formwork height: 15'-0" (4.57 m)



Tying at the panel joint (in the panel)





C Universal waling at an angle

Formwork height: 12'-0" (3.66 m)**Tying at the panel joint (in the filler)**

D Universal waling at an angle

90 degree corners

The corner solutions are based on the strong, torsion-proof **Frami S Xlife inside corner**.



a ... 12" (30.5 cm)

There are **2 ways** of forming right-angled **outside corners**:


- with a Frami S Xlife universal panel
- with a Frami outside corner

Note:

For details regarding extra clamps on outside corners (for increased tensile loads) see 'Inter-panel connections for increased tensile loads'.

with a Frami outside corner


The Frami outside corner is an easy and problem-free way of forming corners in narrow trench situations or where large wall thicknesses are called for.



Required numbers of Frami clamps and Frami clip:

	Up to a wall thickness of		
	16" (41 cm)	24" (61 cm)	30" (76 cm)
Outside corner 3'-0"	4	4	4
Outside corner 4'-0"	6	6	6
Outside corner 6'-0"	6	8	8 + 4 ¹⁾
Outside corner 9'-0"	10	12	12 + 4 ¹⁾

¹⁾ Number of Frami clips



a ... 16" (40.6 cm)

b ... 12" (30.5 cm)

A Frami S Xlife inside corner

B Frami S outside corner

C Frami clamp


D Frami adjustable clamp

E Frami universal waling

F Frami S steel filler


G Frami S Xlife panel 2'-0"

H Frami S Xlife panel 2'-0"

Example with a wall thickness of 28" (71 cm)

a ... 28" (71 cm)

- A** Frami S Xlife inside corner
- B** Frami S outside corner
- C** Frami clamp + Frami clip
- D** Frami adjustable clamp
- E** Frami universal waling
- F** Frami S steel filler
- G** Frami S Xlife panel 3'-0"
- H** Frami S Xlife panel (max. 2'-0")


Example with a wall thickness of 30" (76 cm)

a ... 30" (76 cm)


- A** Frami S Xlife inside corner
- B** Frami S outside corner
- C** Frami clamp + Frami clip
- D** Frami universal waling
- E** Framax S universal waling
- F** Frami S Xlife panel 3'-0"
- G** Frami S Xlife panel 6"
- H** Frami S Xlife panel (max. 2'-0")

with a Frami S Xlife universal panel

When a universal panel is used, a wall-thickness grid with 2" (5.1 cm) increments is available.




Achievable wall thicknesses in 2" (5.1 cm) grid:



Required numbers of Frami universal fixing bolts + Super plates 15.0:

Universal panel 3'-0"x3'-0"	2
Universal panel 3'-0"x4'-0"	3
Universal panel 3'-0"x6'-0"	4
Universal panel 3'-0"x9'-0"	6



a ... 12" (30.5 cm)
b ... 16" (40.6 cm)

- A Frami S Xlife inside corner
- B Frami S Xlife universal panel
- C Frami universal fixing bolt + Super plate 15.0
- D Frami clamp
- E Frami S Xlife panel 2'-0"


Note:

Close off unneeded grid holes in the form-facing of the universal panels with **Frami plugs**.


Note:

When steel fillers are used, it is also possible to handle wall thicknesses of up to 24" (61 cm).

T-junction with Frami inside corner



Wall thicknesses up to 20" (50.8 cm)



a ... 12" (30.5 cm)


A Frami S Xlife inside corner

B Frami clamp

C Frami S Xlife panel 3'-0"

Where 4" steel fillers are used on both sides, wall thicknesses of up to 20" (50.8 cm) can be formed.

Wall thicknesses up to 30" (76.2 cm)



a ... 30" (76.2 cm)

A Frami S Xlife inside corner

B Frami clamp

C Frami S Xlife panel 3'-0"

D Frami S Xlife panel 1'-6"


E Multi-purpose waling WS10 Top50 6'-0"

F Frami universal waling

Chamfer edges

with Frami frontal triangular ledge

The Frami frontal triangular ledge can be pushed over the end face of the panel (no nails needed). For forming outside corners, it is used with the universal panel (integrated slot grid for universal fixing bolts). It is also possible to form edges using the triangular chamfer, of course.




a ... 3/4" (20 mm)

- A** Frami S frontal triangular ledge 3/4" or triangular chamfer
- B** Frami universal fixing bolt
- C** Super-plate 15.0
- D** Frami S Xlife universal panel
- E** Frami S Xlife panel

with triangular chamfer

Where outside corners are formed using the Frami outside corner, the Frami clamps used for the interconnection mean that the triangular chamfer has to be used here.




- A** Frami S outside corner
- B** Frami clamp
- C** Frami S Xlife panel
- D** Triangular chamfer
- E** Wire nail

Triangular chamfers can also be used on corners formed using the Universal panel.

Pilasters

Pilasters can be formed quickly using the Frami S Xlife pilaster panels.




a ... 24" (61 cm)

b ... 6" (15.2 cm)

The Frami S Xlife pilaster panel permits pilaster depths of up to 20" (51 cm), in 2" (5.1 cm) increments, and of up to 24" (61 cm) when outside corners are used.

2 positions / functions:


- bolted in place at right-angles → for pouring



c ... max. 24" (61 cm)

d ... 8" - 20" (20.3 - 51 cm)

- folded closed → for stripping and resetting the formwork



- A** Frami S Xlife pilaster panel
- B** Frami universal fixing bolt 5-12cm
- C** Super-plate 15.0
- D** Frami S Xlife panel
- E** Frami S Xlife panel > 6" (without filler)

Required number of connectors per pilaster:


Panel height	Universal fixing bolts + Super-plates 15.0
3'-0"	4
4'-0"	4
6'-0"	6
9'-0"	8



To ensure that the formwork can be lifted safely, bolt the Frami S Xlife pilaster panel in the 'folded closed' position.

T-junction with Frami S Xlife pilaster panel


Wall thicknesses from 26" to 28" (66 to 71 cm)



a ... 26" to 28" (66 to 71 cm)

- A** Frami S Xlife pilaster panel
- B** Frami S Xlife panel 3'-0"
- C** Frami S steel filler
- D** Frami adjustable clamp
- E** Frami universal waling

Wall thicknesses up to 30" (76.2 cm)



a ... 30" (76.2 cm)

- A** Frami S Xlife pilaster panel
- B** Frami S Xlife panel 3'-0"
- C** Frami S Xlife panel 6"
- D** Frami clamp
- E** Multi-purpose waling WS10 Top50 6'-0"

Shaft formwork



Shaft formwork with Bias-cut corner I

The **Framax bias-cut corner I** is used to form right-angled inside corners in the shaft.

With it, the entire shaft formwork unit is detached from the wall in one piece and then repositioned by crane.



Product features:

- No negative impression in the concrete.
- Formwork set-up and stripping function integrated in the inside corner (no need for crane – uses stripping spindles).
- Entire shaft formwork unit is lifted and reset in one piece (with lifting hooks and four-part lifting chain).



a ... 12" (30 cm)

Stripping play:



a ... 1 1/8" (30 mm)
b ... 2 1/4" (60 mm)

- A Framax S bias cut corner I
- B Framax stripping spindle I with ratchet
- C Steel form-facing


Position of fillers (fitting-timbers) in the inside shaft formwork:

- whenever possible, not directly next to the bias-cut corners

Joining gangs

The Framax bias-cut corner I is joined onto the Frami Xlife panels by means of **Framax quick-acting clamps RU**.

The **difference in thickness between the profiles** is bridged here by the **Frami profile adapter**.



D Frami profile adapter for Bias-cut corner I

E Framax quick-acting clamp RU

Number of Framax quick-acting clamps RU needed:

Height of Bias-cut corner I	Panel height	Number of clamps
1.35 m	3'-0"	4
1.35 m	4'-0"	4
2.70 m	6'-0"	6
2.70 m	9'-0"	6




NOTICE

In order to obtain the full available stripping-play, make sure that the Framax quick-acting clamps RU are mounted at staggered heights (i.e. not opposite one another).

Tying the panels

When tying the shaft formwork, the **tie-hole positions of the Frami Xlife panels** should be used.


The **difference in thickness between the profiles** is bridged here by the **Frami tie-adapter**.



F Frami tie-adapter for Bias-cut corner I

Vertical stacking of Framax bias-cut corners I

- 1) Pull out the coupling bolt.
- 2) Maneuver the Bias-cut corner I into place so that it is flush with the one below it.
- 3) Push the coupling bolt back in.
- 4) Bolt the Bias cut corners I together with two hexagonal bolts.



A Coupling bolt


B Bias-cut corner I

C Hexagonal bolt M16x45 (or $\frac{5}{8} \times 1 \frac{3}{4}$ ")

Animation: <https://player.vimeo.com/video/256373947>

Mounting the Framax stripping spindle I

- 1) Pull out the U-bolt from the stripping spindle.
- 2) Place the stripping spindle on the centering stud of the bias-cut corner.
- 3) Twist the stripping spindle clockwise until fully engaged.
- 4) Position the ratchet between the holes in the push-rod.
- 5) Fix the stripping spindle with the U-bolt.



A Framax stripping spindle I with ratchet

B U-bolt

C Centering stud of bias-cut corner


D Ratchet

E Push-rod

Animation: <https://player.vimeo.com/video/256374622>

Operating the Framax stripping spindle I with ratchet


- Screw a Tie-rod 15.0mm into the Weldable coupler 15.0 of the ratchet.
- **Setting up:**
 - shift the change-over lever into the 'L' position
 - turn the ratchet **clockwise**.
- **Stripping:**
 - shift the change-over lever into the 'R' position
 - turn the ratchet **anti-clockwise**.



- A Tie-rod 15.0mm
- B Weldable coupler 15.0
- C Ratchet
- D Change-over lever




You can also use a **formwork hammer** to operate the ratchet, instead of a Tie-rod 15.0mm.




Lifting by crane

Frami lifting hook



Follow the additional directions in the Operating Instructions!

Lifting by crane:



β max. 15°

- A Frami lifting hook
- B Four-part lifting tackle



The crane hook on the Bias-cut corner I must not be used for lifting the shaft formwork.

- The shaft formwork may only be reset **using lifting hooks**.

Permitted weight of the shaft formwork:
2000 kg (4400 lbs) with 4 Frami lifting hooks




Use a lifting beam for repositioning large gang-forms.

Doka shaft platform

With its telescopic shaft beams, this platform can accommodate any dimension of structure. The inside formwork can be 'parked' on the platform and repositioned together with the platform.

The Frami panel shoe provides increased stability on shaft platforms.





E Frami panel shoe



Follow the directions in the 'Shaft platform' User Information booklet.

Acute and obtuse-angled corners

Frami also has the perfect solution ready for acute and obtuse-angled corners - the Frami hinged corners.



Note:

The Hinged outside corner A (galvanized) cannot be combined with the Hinged outside corner A (powder-coated).

N° of universal walings in the outside and inside corners:

Panel height	N° of universal walings
3'-0"	4
4'-0"	4
6'-0"	4
9'-0"	8

Position of the universal walings:

In every support level of the Hinged inside corner I.

Note:

For angles of less than 120°, no universal walings are needed in inside corners.



NOTICE


For details regarding extra clamps on outside corners (for increased tensile loads) see 'Inter-panel connections for increased tensile loads'.

Note:

Acute-angled (pointed) corners are tied using the Form-tie system 15.0 (5/8"Ø). This makes it possible to form angles of as little as 60°.

60° - 135° angles, with hinged corners

I + A




NOTICE


If there are fillers, fit extra Universal walings as shown in 'Length adjustment using fillers'.

Number of Frami clamps needed in the whole hinged outside corner (i.e. for both sides):

Panel height	Width of panel next to hinged outside corner up to 2'-0"	Width of panel next to hinged outside corner up to 3'-0"
3'-0"	4	4
4'-0"	4	6
6'-0"	6	8
9'-0"	8	12





- A** Frami S hinged outside corner A
- B** Frami S hinged inside corner I
- C** Frami S Xlife panel
- D** Frami clamp
- E** Frami universal waling 1.25m
- F** Frami wedge clamp
- G** Form-tie



- A** Frami S hinged outside corner A
- B** Frami S hinged inside corner I
- C** Frami S Xlife panel
- D** Frami clamp
- E** Frami universal waling
- F** Frami wedge clamp
- G** Form-tie

135° - 180° angles, with hinged inside corner I only



- A** Frami S hinged inside corner I
- B** Frami clamp
- C** Frami universal waling
- D** Frami wedge clamp
- E** Form-tie
- F** Frami S Xlife panel


Bulkhead formwork

There are **4 possible ways** of forming **bulkheads**:

- with Universal walings
- with stop-end waler ties
- with an Xlife universal panel and an outside corner
- with an Xlife panel and an outside corner

with Universal walings

The Universal waling makes it possible to form bulkheads continuously across any thickness of wall. The Universal walings are mounted using Universal fixing bolts 5-12cm and Super plates 15.0.



Frami universal fixing bolt:

Permitted tensile load:

2.92 kip (13.0 kN) when used in the Xlife panel

3.51 kip (15.6 kN), when used in the Xlife universal panel

Frami universal waling:


Permitted moment: 0.96 kip-ft (1.3 kNm)

Framax S universal waling:

Permitted moment: 3.85 kip-ft (5.2 kNm)

Note:

For details regarding extra clamps on bulkheads (for increased tensile loads) see the section headed 'Inter-panel connections for increased tensile loads'.



A Frami universal waling or Framax S universal waling



B Universal fixing bolt 5-12cm



C Super plate 15.0

D Frami S Xlife panel > 6"

E Form tie



Positioning the Universal walings where the formwork height is 9'-0" (2.74 m):

Up to wall thickness 16" (40 cm)	Up to wall thickness 24" (61 cm)
3 Frami universal walings	5 Frami universal walings
	

Up to wall thickness 28" (71 cm)	Up to wall thickness 30" (76 cm)
4 Framax S universal walings	5 Framax S universal walings
	

with stop-end waler ties

The Frami stop-end waler tie 15-45cm lets you form bulkheads steplessly, from wall thicknesses of 6" (15 cm) to 18" (45 cm).



a ... 6" (15 cm) to 18" (45 cm)

b ... ≥ 8" (20 cm)

A Frami stop-end waler tie 15-45cm


B Frami S Xlife panel

Required numbers of Frami stop-end waler ties 15-45cm:



Panel height (upright panels)	Frami stop-end waler tie 15-45cm
3'-0"	1 ^{*)}
4'-0"	2
6'-0"	2
9'-0"	3

Panel width (horizontal panels)	Frami stop-end waler tie 15-45cm
6" to 2'-6"	1 ^{*)}
3'-0"	2

^{*)} On single panels not forming part of a gang (e.g. when being used as footing and grade-beam formwork), at least 2 stop-end waler ties must be used.

Positioning the stop-end waler ties:**with an Xlife universal panel and an outside corner**

The continuous hole grid on the Universal panels makes it possible to form bulkheads in 2" (5.1 cm) increments.



- A Frami S Xlife universal panel
- B Frami universal fixing bolt 5-12cm
- C Super-plate 15.0
- D Frami S outside corner
- E Frami clamp
- F Frami S Xlife panel



Required numbers of connectors:

Panel height	Universal fixing bolt + Super-plate	Frami clamp
3'-0"	2	4
4'-0"	2	4
6'-0"	3	6
9'-0"	4	8

The values given here apply up to a wall thickness of 24" (61 cm).

with an Xlife panel and an outside corner

For walls whose thickness corresponds exactly to the panel width.



- A** Frami S Xlife panel
- B** Frami S outside corner
- C** Frami clamp

Required numbers of Frami clamps per bulkhead:


Panel height	Frami clamp
3'-0"	8
4'-0"	8
6'-0"	12
9'-0"	16

The values given here apply up to a wall thickness of 24" (61 cm).

Wall junctions

Right-angled connections

with an Xlife universal panel:



A Frami S Xlife universal panel


B Tie-rod 15.0mm

C In-place timber brace

Number of form-ties:

Form-tie position X	Xlife universal panel			
	3'-0"	4'-0"	6'-0"	9'-0"
Up to 6" (15 cm)	2	2	3	4
Up to max. 10" (25 cm)	2	2	4	6

with Xlife panel and dimensional lumber:



A Frami S Xlife panel

B Dimensional lumber, max. 4" (10 cm)

C Universal waling – not needed if the squared timber is less than 2" (5 cm) wide


D Form-tie

E Form-tie

F In-place timber brace

In-line connections


with an Xlife universal panel:



A Frami S Xlife universal panel

B Tie-rod 15.0mm

with Xlife panel and dimensional lumber:



a ... max. 2" (5 cm)


A Frami S Xlife panel

B Dimensional lumber

C Adjustable clamp

D Form-tie

with Xlife panel 1'-0":



a ... max. 8" (20 cm)


A Frami S Xlife panel 1'-0"

B Frami universal waling 1.25m

C Frami wedge clamp

D Form-tie

with an Xlife panel from the previous casting section:




A Frami S Xlife panel

B Form-tie

Corner connections

with Xlife panel and dimensional lumber:



A Frami S Xlife panel

B Dimensional lumber, max. 4" (10 cm)

C Frami S Xlife panel 6"


D Universal walings – not needed if the squared timber is less than 2" (5 cm) wide

E Frami wedge clamp

F Frami clamp

G Form-tie

H In-place timber brace



A Frami S Xlife panel

B Dimensional lumber, max. 2" (5 cm)

C Dimensional lumber

D Adjustable clamp

E Form-tie


F In-place timber brace

Inter-panel connections for increased tensile loads

As a basic rule, only **3 clamps are needed per 9'-0" panel height**, and **2 clamps per 6'-0", 4'-0" and 3'-0" panel height**, as tension links between the panels. However, where **increased tensile loads** need to be sustained near outside corners and stop-ends, **extra clamps are needed**.

Near bulkheads


for wall thicknesses from 16" to 24" (40 to 61 cm)



a ... 16" to 24" (40 to 61 cm)

Panel height	Number of clamps
	In zone "X1" (panel joints within 6'-0" (1.8 m) of a bulkhead)
9'-0"	3 + 1
6'-0"	2 + 1
4'-0"	2
3'-0"	2

for wall thicknesses of over 24" and up to 30" (61 cm and up to 76 cm)





a ... up to 30" (76 cm)

Panel height	Number of clamps
	In zone 'X1' (panel joints up to 6'-0" (1.8 m) away from a bulkhead)
9'-0"	3 + 2
6'-0"	2 + 1
4'-0"	2
3'-0"	2

Near outside corners



for panel widths up to 2'-0"



e ... up to 2'-0" (panel width)

Panel height	Number of clamps
	In zone 'X1' (panel joints within 6'-0" (1.8 m) of an outside corner)
9'-0"	3 + 1
6'-0"	2 + 1
4'-0"	2
3'-0"	2


for panel widths over 2'-0" and up to 3'-0"



e ... > 2'-0" up to 3'-0" (panel width)

Panel height	Number of clamps	
	In zone 'X1' (panel joints up to 6'-0" (1.8 m) from an outside corner)	In zone 'X2' (panel joints 6'-0" to 10'-0" (1.8 to 3.0 m) from an outside corner)
9'-0"	3 + 3	3 + 1
6'-0"	2 + 2	2 + 1
4'-0"	2 + 1	2
3'-0"	2	2

for panel widths of over 3'-0" and up to 3'-6"



e ... > 3'-0" up to 3'-6" (panel width)

Panel height	N° of clamps		
	In zone 'X1' (panel joints up to 6'-0" (1.8 m) from an outside corner)	In zone 'X2' (panel joints 6'-0" to 9'-0" (1.8 to 2.74 m) from an outside corner)	In zone 'X3' (panel joints 9'-0" to 12'-0" (2.74 to 3.65 m) from an outside corner)
9'-0"	3 + 3	3 + 2	3 + 1
6'-0"	2 + 2	2 + 1	2 + 1
4'-0"	2 + 1	2	2
3'-0"	2	2	2

Vertical stacking of panels

Positions of the connecting and tying components and other accessories needed for:

- lifting and setting down
- crane-handling
- pouring platform
- pouring

Note:

Follow the directions in the section headed 'Form-tie system'.

Frami clamp:


Permitted tensile force: 2.245 kip (10.0 kN)

Permitted shear force: 1.12 kip (5.0 kN)

Permitted moment: 0.15 kip-ft (0.20 kNm)

Frami universal waling:

Permitted moment: 0.96 kip-ft (1.3 kNm)



A Tie-rod + Super-plate 15.0

B Frami clamp

C Frami wedge clamp

D Frami universal waling 1.25m



NOTICE


Do not oil or grease wedge-clamped joints.

Note:

When panels are vertically stacked, the arrows point upward.


Formwork height:

6'-0" to 8'-0" (183 to 244 cm)



Formwork height:

7'-6" to 9'-0" (228 to 274 cm)




NOTICE

Stack max. 3'-0" on top of one 6'-0" high basic panel!


Formwork height:

8'-6" and 9'-0" (259 and 274 cm)




Formwork height:


9'-6" and 10'-0" (289 and 305 cm)




Formwork height:
10'-0" (305 cm)




Formwork height:
10'-6" to 12'-0" (320 to 365 cm)



Formwork height:
12'-0" (365 cm)




Formwork height:
12'-0" (365 cm)




A Framax S universal waling 1.50m

B Frami profile connector 5-18cm + Super plate 15.0


Formwork height:
12'-6" and 13'-0" (381 and 396 cm)




Formwork height:
13'-0" (396 cm)




Formwork height:
13'-6" to 15'-0" (411 to 457 cm)




Formwork height:
15'-0" (457 cm)




Formwork height:
14'-6" and 15'-0" (442 and 457 cm)




Formwork height:
15'-6" and 16'-0" (472 and 487 cm)




Formwork height:
15'-6" and 16'-0" (472 and 487 cm)




Formwork height:
16'-6" to 18'-0" (503 to 548 cm)



Formwork height:
16'-6" to 18'-0" (503 to 548 cm)




Formwork height:
18'-0" (548 cm)




Note:

When adding narrow gangs, observe the following rules for vertical stacking of panels:




Other combinations require correspondingly more connector components.

The illustrations given here show the most economical solutions for each formwork height.


**Formwork height:
22'-0" (670 cm)****Note:**

The accessories shown here must also be used for a formwork height of 21'-0" (640 cm)


Formwork height:
24'-0" (731 cm)



Formwork height:
27'-0" (823 cm)



Plumbing accessories



98032-233-01

The plumbing accessories ensure that the formwork remains stable against wind loads, and make it easier to plumb and align the formwork.



NOTICE

The formwork gangs must be securely braced in **every** phase of the construction work!

Observe all applicable safety rules!



For more information (wind loads etc.) see the section headed 'Vertical and horizontal loads' in the Calculation Guide 'Doka formwork engineering'.



CAUTION

There is a risk of the formwork tipping over in **high winds**.

► If high wind speeds are likely, and when work finishes for the day or before prolonged work-breaks, always take extra precautions to fix the formwork in place.

Suitable precautions:

- set up the opposing formwork
- place the formwork against a wall
- anchor the formwork to the ground

The rule-of-thumb here is:

The length of the struts or pipe-braces should be the same as the height of the panel to be supported.

Note:

Every gang-form must be supported by **at least 2 plumbing accessories**.

Max. influence widths of the struts or pipe-braces:

Formwork height	Plumbing strut / Prop / Pipe brace	Max. influence width assuming wind pressure of	
		10 psf (0.48 kN/m ²)	15 psf (0.72 kN/m ²)
6'-0" (1.83 m)	260	9'-0" (2.75 m)	6'-0" (1.83 m)
9'-0" (2.75 m)	260	9'-0" (2.75 m)	6'-0" (1.83 m)
12'-0" (3.66 m)	340	12'-0" (3.65 m)	9'-0" (2.75 m)
15'-0" (4.57 m)	540 ¹⁾	15'-0" (4.55 m)	10'-0" (3.05 m)
18'-0" (5.48 m)	540 ¹⁾	10'-6" (3.20 m)	6'-9" (2.05 m)
21'-0" (6.40 m)	340 + 22'-0"-40'-0" ²⁾	12'-0" (3.65 m)	9'-0" (2.75 m)
22'-0" (6.70 m)	340 + 22'-0"-40'-0" ²⁾	12'-0" (3.65 m)	9'-0" (2.75 m)
24'-0" (7.31 m)	340 + 22'-0"-40'-0" ²⁾	10'-6" (3.20 m)	6'-9" (2.05 m)
27'-0" (8.23 m)	540 ¹⁾ + 22'-0"-40'-0" ²⁾	12'-0" (3.65 m)	9'-0" (2.75 m)
Max. anchoring load: 3 kip (13.5 kN)			

¹⁾ or Pipe brace 12'-0"-21'-0"

²⁾ or Eures 60 550

Values apply to all panel struts in conjunction with the **Frami S bracing head** or the **Frami S connection profile**.

These values apply up to wind-pressures of 10 psf (0.48 kN/m²) or 15 psf (0.72 kN/m²) respectively. The greater wind loads encountered at exposed formwork-ends must be constructionally sustained by additional plumbing accessories (e.g. struts or pipe-braces). The number of struts must be determined separately for:

- wind pressure above 15 psf (0.72 kN/m²)
- formwork higher than 27'-0" (8.23 m)

Sample calculation:

- Formwork height: 27'-0" (8.23 m)
- Width of gang-form: 21'-0" (6.40 m)
- Wind pressure: 10 psf (0.48 kN/m²)




Result:

- 2 Struts 540
(or 2 pipe braces 12'-0"-21'-0")
and
- 2 pipe braces 22'-0"-40'-0"
(or 2 Eures 60 550)

Fixing to the floor

- Anchor the plumbing accessories in such a way as to resist tensile and compressive forces!


Boreholes in the footplates

Plumbing strut 260	Struts 340 / 540	Pipe brace (pipe brace shoe)
 9723-288-01	 9727-343-01	 9762-358-01

- a ... 1" diam. (26 mm)
 b ... 1 1/16" diam. (18 mm) (suitable for Doka express anchor)
 c ... 1 1/16" diam. (27 mm)
 d ... 1 3/16" diam. (20 mm) (suitable for Doka express anchor)

Anchoring the footplate

The **Doka Express anchor** can be re-used many times over.



- A** Doka Express anchor 16x125mm
B Doka coil 16mm

Cylinder compressive strength of concrete:
 min. 3,000 psi (20 N/mm²)




Follow the Fitting Instructions!

Required safe working load of alternative anchor for foot-plates: min. 3.0 kip (13.5 kN)
 Follow the manufacturer's applicable fitting instructions.

- Use the nail-holes to fasten the panels to the ground or sills.

Plumbing strut 260



- a ... min. 4'-9" - max. 8'-6" (min. 147 - max. 257 cm)
 α ... approx. 60°

A Plumbing strut 260 IB

B Strut head EB

Max. influence widths of Plumbing strut 260:


Formwork height	Max. influence width assuming wind pressure of	
	10 psf (0.48 kN/m ²)	15 psf (0.72 kN/m ²)
6'-0" (1.83 m)	7'-6" (2.30 m)	5'-0" (1.50 m)
9'-0" (2.75 m)	5'-0" (1.50 m)	3'-6" (1.05 m)
Max. anchoring load: 1 kip (4.5 kN)		

The values given here apply to Plumbing struts 260 with a **Strut head EB**.


These values apply up to wind-pressures of 10 psf (0.48 kN/m²) or 15 psf (0.72 kN/m²) respectively. The greater wind loads encountered at exposed formwork-ends must be constructionally sustained by additional plumbing accessories (e.g. struts or pipe-braces).

Fixing the struts to the formwork


- Fit the Strut head onto the Plumbing strut.



- Pin the Strut head into the holes in the **cross profiles (frame profiles)**.



Strut 340




a ... min. 6'-4" - max. 11'-2" (min. 191 - max. 342 cm)
 α ... approx. 60°

A Plumbing strut 340 IB EF

B Prop shoe EB

C Frami S bracing head EB or Frami S connection profile EB

Strut 540




a ... min. 10'-2" - max. 18'-0" (min. 310 - max. 549 cm)
 α ... approx. 60°

A Plumbing strut 540 IB EF

B Prop shoe EB

C Frami S bracing head EB or Frami S connection profile EB

Pipe brace 12'-0"-21'-0"



a ... min. 12'-0" - max. 21'-0" (min. 366 - max. 640 cm)
 α ... approx. 60°

A Pipe brace 12'-0"-21'-0"


B Speed bolt 3/4"x4"

C Speed nut 3/4"

D Pipe brace shoe

E Frami S bracing head EB or Frami S connection profile EB

Pipe brace 22'-0"-40'-0"



a ... min. 22'-0" - max. 40'-0" (min. 670 - max. 1219 cm)
 b ... min. 6'-4" - max. 11'-2" (min. 191 - max. 342 cm)
 α ... approx. 60°

A Pipe brace 22'-0"-40'-0"

B Speed bolt 3/4"x4"

C Speed nut 3/4"

D Pipe brace shoe

E Frami S bracing head EB or Frami S connection profile EB


Fixing the struts to the formwork

with Frami S bracing head

The Frami S bracing head allows bracing to be attached to the frame profile.


Fixing the Frami S bracing head to Struts 340 / 540 (A)

- ▶ Attach the Frami S bracing head to the strut with the included bolt and spring cotter.



Fixing the Frami S bracing head to the Pipe brace (B)

- ▶ Attach the Frami S bracing head to the pipe brace using a speed bolt and speed nut.



A Strut 340 / 540


B Pipe brace 12'-0"-21'-0"

C Speed bolt 3/4"x4"


D Speed nut 3/4"

Attaching the Frami S bracing head to the frame profile



- 1) Place the bracing head onto an empty cross profile.
- 2) Slide the bracing head until it is flush with the frame profile.
The stud-pins will slide into the cross boreholes of the frame profiles.
- 3) Push the U-bolt to secure the head in place.





Possible connection points on vertically and horizontally placed panels



On a vertically placed panel



On a horizontally placed panel




with Frami S connection profile


This connection method is used on column formwork, circular formwork and wherever it is not possible to attach the Frami S bracing head to the frame profile. The Connection profile is suitable for use on standard Xlife panels and Xlife universal panels.

- Use Frami wedge clamps to fasten the Frami S connection profile in the cross boreholes of the **cross-profiles or frame profiles**.


On standard Xlife panels



On Xlife universal panels



On the panel joint (stacked horizontally)





- A** Frami S connection profile EB
- B** Frami wedge clamp

Attaching the struts to the Frami S connection profile



The connection profile has connection points for the Pipe brace and for the Struts 340 / 540.

- Guide the Pipe brace to the appropriate connection point and fix it on with a speed bolt and a speed nut.
- If using Struts 340 / 540, attach the Frami S connection profile with a bolt and a spring cotter.



Strut 340 / 540	Pipe brace
On standard Xlife panels	



On Xlife universal panels




On the panel joint (stacked horizontally)



- A** Frami S connection profile EB
- B** Strut 340 / 540
- C** Pipe brace 12'-0"-21'-0" or 22'-0"-40'-0"

Pouring-platforms with single brackets



98032-232-01

The Frami brackets 60 enable you to assemble pouring platforms that can easily be mounted by hand.

Preconditions for use:

Only fix the pouring platform onto formwork constructions that are sufficiently stable to transfer the expected loads.

Also brace the formwork in a windproof manner when erecting it and when it is temporarily 'parked' in the standing position.

Ensure that the formwork gang has sufficient stiffness.

Observe all applicable safety rules.

with Frami bracket 60

The Frami bracket 60 is a 'use-anywhere' bracket for making pouring platforms (platform width 2'-0" (60 cm)).

Note:

The scaffold planks and guard-rail material shall meet or exceed any local, state, provincial or national regulations.

Plank thicknesses for support centers of up to 6'-6" (2.00 m):

- 2 scaffold planks 2 x 10, min. 1 1/2 x 9 1/2" (4 x 24 cm)
- 1 scaffold plank 2 x 6, min. 1 1/2 x 5 1/2" (4 x 14 cm)
- 2 guard-rail planks 2 x 4, min. 1 1/2 x 3 1/2" (4 x 9 cm)
- 1 guard-rail plank 2 x 6, min. 1 1/2 x 5 1/2" (4 x 14 cm) (toe-board)

Fastening the scaffold planks:

with 3 carriage bolts 3/8-16 x 4 3/4 (cup square screws M 10x120) per bracket (not included with product).

Fastening the guard-rail boards: Use nails

Permitted service load: 25 psf (120 kg/m²)

Max. influence width: 6'-0" (1.80 m)

Complies with the following Standards:

- OSHA 1926, Subpart L
- CAN/CSA S269.2 - 'Access Scaffolding for Construction Purposes' (light-duty scaffolds)



NOTICE


The brackets must be secured against accidental lift-out



NOTICE

Multi-panel gangs without an opposing formwork and with pouring platforms must be fixed on the ground so as to prevent slippage.

On upright panel (fixed in the cross profile)



h ... 3'-7" (110 cm)

A Frami bracket 60


B Upright panel

C Spring cotter (protection against accidental lift-out)

Note:


The bracket must NOT be fixed in the circular hole in the middle of the cross profile.

On horizontal panel (fixed in the cross profile)



- A** Frami bracket 60
- B** Horizontal panel
- D** Fastening pin with linch pin (protection against accidental lift-out)

On upright or horizontal panel (fixed in the frame profile)



- A** Frami bracket 60
- B** Horizontal panel
- C** Spring cotter (protection against accidental lift-out)


When the platform is fixed in the frame profile, the formwork does not provide any fall protection.

- For this reason, mount an opposing guard-rail on the opposing formwork.

Sideguards on exposed platform-ends

On pouring scaffolds that do not completely encircle the structure, suitable sideguards must be placed across exposed end-of-platform zones.

Handrail clamp S



- A** Handrail clamp S
- B** Guard-rail plank min. 2x4 (1 1/2" x 3 1/2" (4 x 9 cm)), site-provided
- C** Guard-rail plank min. 2x6 (1 1/2" x 5 1/2" (4 x 14 cm)), site-provided
- D** Frami bracket 60

Note:

The scaffold planks and guard-rail material shall meet or exceed any local, state, provincial or national regulations.

The sideguard consists of:

- 2 Handrail clamps S
- 2 guard-rail planks min. 1 1/2" x 3 1/2" (4 x 9 cm), site-provided
- 1 guard-rail plank min. 1 1/2" x 5 1/2" (4 x 14 cm), site-provided

How to mount:

- Fasten the handrail clamps to the deck planking of the pouring scaffold, using the wedge (clamping range 1" - 1'-5" (2 to 43 cm)).
- Secure the guardrail planks to the loops on the handrail clamps with one d10 (28x65) nail per loop.




Follow the directions in the User Information booklet 'Handrail clamp S'!

Lifting by crane

Safe crane-handling of Frami is made possible by the Doka 4-part chain 3.20m and the Frami lifting hook. The lifting hook locks automatically after being hung into place.

Doka 4-part chain 3.20m




- Attach the Doka 4-part chain 3.20m to the Frami lifting hooks.
- Hang the remaining chain-lengths back in place.

Max. load-bearing capacity (as 2-part chain):
Up to spread-angle β of 30°: 5,200 lbs (2,400 kg).



Follow the directions in the Operating Instructions!

Frami lifting hook



Max. load:

- Spread-angle β up to 7.5°:
1650 lbs (750 kg) per Frami lifting hook
Feasible formwork area with 2 lifting hooks: approx. 405 sq.ft. (37.5 m²)
- Spread-angle β up to 30°:
1100 lbs (500 kg) per Frami lifting hook
Feasible formwork area with 2 lifting hooks: approx. 270 sq.ft. (25 m²)

Frami lifting hooks with the rated load-bearing capacity of max. 1100 lbs (500 kg) also comply with the requirements for a load bearing capacity of 1650 lbs (750 kg) at a spread angle $\beta \leq 7.5^\circ$.



Follow the additional directions in the Operating Instructions!

Securing the lifting hooks against slipping sideways




NOTICE


Position the lifting hooks so that they cannot slip sideways.

- over **inter-panel joints**
- over **cross profiles** (single panels incorporated in the horizontal)
- in **corner-tie pockets** (e.g. gangs with only two panels joined together longside vertically)
- or **secure with bolts**

Frami S Xlife panel



Frami S Xlife universal panel



A Frami lifting hook

B Corner-tie pocket

C Hexagon bolt DIN 933 M18x50 8x8 galv.

D Hexagon nut DIN 934 M18 8 galv.


Position of the lifting hooks

Note:


The positions of the lifting hooks as shown here also apply for gangs incorporating vertically stacked panels.

Single panel:

Panel width of up to 2'-0"




Panel width of over 2'-0"




B Corner-tie pocket

Panel 8'-0"x9'-0"




Gang-form - Two panels longside vertical:

Variant 1:




Variant 2:




B Corner-tie pocket

Gang-form - Three (or more) panels longside vertical:



E Panel joint

Gang-form - Panel longside horizontal (vertically stacked):



F Cross profile

Transporting, stacking and storing

Bundling the panels


- 1) Place sleepers (W x H approx. 4" x 4" (10 x 10 cm)) under the cross profile.
- 2) Strap the sleepers (hardwood blocking) and the bottom panel together with metal banding.



CAUTION

- Stack max. 10 panels on top of one another (results in a stack height, incl. sleepers, of approx. 3'-4" (100 cm)).

- 3) Strap the whole stack together tightly with metal banding.




98032-318-01

Transporting the panels

Dokamatic lifting strap 13.00m

The Lifting strap 13.00m is a practical tool for **offloading and loading trucks**, and for **lifting and setting down** stacks of panels.



98032-319-01



With closely stacked bundles of panels:

- lever up the bundle (e.g. with a piece of dimensional lumber (**D**)), to make a space for threading in the lifting equipment.

Caution!

When doing this, always make sure that the bundle of panels remains stable!



WARNING

- The Lifting straps 13.00 m may only be used as shown here if there is no risk of the straps sliding towards one another, or of the load being displaced.

Max. load:
4,400 lbs (2,000 kg) / Dokamatic lifting strap 13.00m




Follow the directions in the Operating Instructions!

Doka 4-part chain 3.20m

The Doka 4-part chain 3.20m is a multi-functional sling means:

- used with the integrated **eye-hooks** for hoisting formwork, platforms and multi-trip packaging containers
- used in conjunction with **Frami transport hook** for hoisting stacks of panels and individual panels



The Doka 4-part chain 3.20m can be adjusted to the center-of-gravity position by shortening the lengths of the individual chains.

Max. load:


	Spread-angle β			
	0°	0°-30°	30°-45°	45°-60°
Using 1 chain	3,000 lbs (1,400 kg)	-	-	-
Using 2 chains	-	5,200 lbs (2,400 kg)	4,400 lbs (2,000 kg)	3,000 lbs (1,400 kg)
Using all 4 chains	-	7,900 lbs (3,600 kg)	6,600 lbs (3,000 kg)	4,600 lbs (2,120 kg)



Follow the directions in the Operating Instructions!

Frami transport hook with Doka 4-part chain 3.20m

Close-up of Frami transport hook



A Frami transport hook

B Doka 4-part chain 3.20m

C Stacking tape

D Strapping tape

Max. lifting capacity:

1000 lbs (450 kg) per Frami transport hook



Frami transport hooks manufactured until 2015, with a stated load capacity of 550 lbs (250 kg), are also capable of carrying 1000 lbs (450 kg).



Follow the directions in the Operating Instructions!

The Frami transport hook plus Doka 4-part chain 3.20m are used for:


- Hoisting bundled stacks of panels
- Lifting panels off the stack
- Handling horizontal (flat) multi-panel gangs



Dimension 'b' (width of gang)	Max. n° of panels across width of gang
up to 6'-0"	no restriction
more than 6'-0"	max. 3 panels

Lifting panels upright / turning panels over

- Use **Frami transport hooks** to lay the framed panel flat on squared timbers 8" x 8" (20 x 20 cm).



- A** Frami transport hook
- B** Doka 4-part chain 3.20m
- C** Squared timber 8" x 8" (20 x 20 cm)




WARNING

Using Frami transport hooks to lift framed panels upright or turn them over is prohibited!

- Use Frami lifting hooks!

- Position the Frami lifting hooks. Lift the framed panel upright with **Frami lifting hooks** and, if applicable, lay it flat with the sheeting side down.



- B** Doka 4-part chain 3.20m
- C** Squared timber 8" x 8" (20 x 20 cm)
- D** Frami lifting hook




Follow the directions in the Operating Instructions!

Utilize the benefits of Doka multi-trip packaging on your worksite.

Our Multi-trip packaging such as transport boxes, stacking pallets, accessory boxes and skeleton transport boxes keep everything in place on the site.

Doka skeleton transport box 1.70x0.80m

Storage and transport device for small items



Max. load-bearing capacity: 700 kg (1540 lbs)
Permitted imposed load: 3150 kg (6950 lbs)

To make the Doka skeleton transport box easier to load and unload, one of its sidewalls can be opened.

Using Doka skeleton transport boxes 1.70x0.80m as storage units

Max. n° of units on top of one another

Outdoors (on the site) Floor gradient up to 3 %	Indoors Floor gradient up to 1 %
2	5
It is not allowed to stack empty pallets on top of one another!	



NOTICE

Stacked multi-trip boxes or pallets must have the heaviest boxes at the bottom and the lightest at the top.


Using Doka skeleton transport boxes 1.70x0.80m as transport devices

Lifting by crane



NOTICE

- Multi-trip packaging items may only be lifted one at a time.
- Only lift the boxes when their sidewalls are closed!
- Use a suitable lifting chain (e.g. Doka 4-part chain 3.20m). Do not exceed permitted load capacity.
- Spread-angle β max. 30°!



9234-203-01


Shifting boxes with the forklift or pallet stacking truck

The forks can be inserted under either the broadside or the narrowside of the containers.

Doka multi-trip transport box


Storage and transport device for small items.

Doka multi-trip transport box 1.20x0.80m



Max. load-bearing capacity: 1500 kg (3300 lbs)
Permitted imposed load: 7850 kg (17300 lbs)

Different items in the Doka multi-trip transport box can be kept separate with the **Multi-trip transport box partitions 1.20m or 0.80m**.




A Slide-bolt for fixing the partition

Possible ways of dividing the box

Multi-trip transport box partition	in the longitudinal direction	in the transverse direction
1.20 m	max. 3 partitions	-
0.80 m	-	max. 3 partitions
	9206-204-02	9206-204-03

Doka multi-trip transport box 1.20x0.80mx0.41m



Max. load-bearing capacity: 750 kg (1650 lbs)
Permitted imposed load: 7200 kg (15870 lbs)

Using Doka multi-trip transport boxes as storage units

Max. n° of units on top of one another

Outdoors (on the site)		Indoors	
Floor gradient up to 3 %		Floor gradient up to 1 %	
Doka multi-trip transport box 1.20x0.80m		Doka multi-trip transport box 1.20x0.80x0.41m	
3	5	6	10
It is not allowed to stack empty pallets on top of one another!			



NOTICE

Stacked multi-trip boxes or pallets must have the heaviest boxes at the bottom and the lightest at the top.


Using Doka multi-trip transport boxes as transport devices

Lifting by crane



NOTICE

- Multi-trip packaging items may only be lifted one at a time.
- Use a suitable crane lifting tackle (e.g. Doka 4-part chain 3.20m). Do not exceed the permitted load-bearing capacity.
- Spread angle β max. 30°!




9206-202-01

Shifting boxes with the forklift or pallet stacking truck

The forks can be inserted under either the broadside or the narrowside of the containers.

Doka stacking pallet 1.55x0.85m and 1.20x0.80m

Storage and transport devices for long items.



Max. load-bearing capacity: 1100 kg (2420 lbs)
Permitted imposed load: 5900 kg (12980 lbs)

Using Doka stacking pallets as storage units

Max. n° of units on top of one another

Outdoors (on the site) Floor gradient up to 3%	Indoors Floor gradient up to 1%
2	6
Do not stack empty pallets on top of one another!	



NOTICE

- Stacked multi-trip boxes or pallets must have the heaviest boxes at the bottom and the lightest at the top.
- How to use with Bolt-on caster set B:**
 - Always apply the fixing brake when the container is 'parked'.
 - When Doka stacking pallets are stacked, the bottom pallet must NOT be one with a bolt-on caster set mounted to it.


Using Doka stacking pallets as transport devices

Lifting by crane



NOTICE

- Multi-trip packaging items may only be lifted one at a time.
- Use a suitable lifting chain (e.g. Doka 4-part chain 3.20m). Do not exceed permitted load capacity.
- Load the items centrically.
- Fasten the load to the stacking pallet so that it cannot slide or tip out.
- Spread-angle β max. 30°!



	a
Doka stacking pallet 1.55x0.85m	max. 4.5 m
Doka stacking pallet 1.20x0.80m	max. 3.0 m

Shifting boxes with the forklift or pallet stacking truck




NOTICE

- Load the items centrically.
- Fasten the load to the stacking pallet so that it cannot slide or tip out.

Doka accessory box

Storage and transport devices for small items.



Max. load-bearing capacity: 1000 kg (2200 lbs)
Permitted imposed load: 5530 kg (12191 lbs)

Using Doka accessory boxes as storage units

Max. n° of units on top of one another

Outdoors (on the site) Floor gradient up to 3%	Indoors Floor gradient up to 1%
3	6
Do not stack empty pallets on top of one another!	



NOTICE

- Stacked multi-trip boxes or pallets must have the heaviest boxes at the bottom and the lightest at the top.
- How to use with Bolt-on caster set B:**
 - Always apply the fixing brake when the container is 'parked'.
 - When Doka stacking pallets are stacked, the bottom pallet must NOT be one with a bolt-on caster set mounted to it.


Using Doka accessory boxes as transport devices

Lifting by crane



NOTICE

- Multi-trip packaging items may only be lifted one at a time.
- Use a suitable crane lifting tackle (e.g. Doka 4-part chain 3.20m). Do not exceed the permitted load-bearing capacity.
- Spread-angle β max. 30°!



92816-206-01


Shifting boxes with the forklift or pallet stacking truck

The forks can be inserted under either the broadside or the narrowside of the containers.

Bolt-on caster set B

The Bolt-on caster set B turns the stacking pallet into a fast and maneuverable transport trolley.

Suitable for drive-through access openings > 90 cm.



The Bolt-on caster set B can be mounted to the following multi-trip packaging items:

- Doka accessory box
- Doka stacking pallets



Follow the directions in the 'Bolt-on castor set B' Operating Instructions!


Column formwork

There are several different ways of using Frami framed formwork to make column formworks:


- with **Xlife universal panels**
 - for flexible accommodation to column cross-sections of up to 32" x 32" (81 x 81 cm) in 2" (5.1 cm) increments
- combining **Xlife universal panels and standard Xlife panels**
 - is a highly economical solution for certain cross-sections of column

- with **Xlife panels and outside corners**
 - for dimensions of 6" (15.2 cm), 12" (30.5 cm), 18" (45.7 cm) and 24" (61 cm)

Permitted pressure of fresh concrete:
1650 psf (80 kN/m²)



Design of column formwork




NOTICE

- To achieve exact plumbing & aligning of the column formwork, the best arrangement of the panel struts is as illustrated here.
- Always attach panel struts to free-standing formwork halves to prevent them from falling over.
- To obtain the highest possible dimensional accuracy, the panels must be pushed apart (i.e. towards the outside) while being assembled.

with Xlife universal panels

The practical 2" (5.1 cm) hole-grid is ideal for forming columns. **Cross-sections of up to 32" x 32" (81 x 81 cm).** By combining panels with heights of 9'-0", 6'-0", 4'-0", 3'-0" and 2'-0", an incremental height grid of 1'-0" (30.5 cm) can be achieved.

Possible cross-sections in a 2" (5.1 cm) increment-grid



Example: 16" x 30" (40.6 x 76.2 cm) column

A Frami S Xlife universal panel

B Frami universal fixing bolt 5-12cm

C Super-plate 15.0

D Frami S frontal triangular ledge 3/4"

Frami universal fixing bolt:


Permitted tensile load:

3.51 kip (15.6 kN), when used in the Xlife universal panel

Note:

Close off unneeded grid holes in the form-facing of the universal panels with **Frami plugs**.

Materials schedule:



Formwork height (H)	Xlife universal panels (A)					Frami clamps (B)	Universal fixing bolts (C)	Super-plates 15.0 (D)
	9'-0"	6'-0"	4'-0"	3'-0"	2'-0"			
9'-0" (2.74 m)	4						24	24
10'-0" (3.05 m)		4	4			8	28	28
11'-0" (3.35 m)	4				4	8	28	28
12'-0" (3.65 m)	4			4		8	32	32
13'-0" (3.96 m)	4		4			8	36	36
14'-0" (4.26 m)	4			4	4	16	36	36
15'-0" (4.57 m)	4	4				8	40	40
16'-0" (4.87 m)	4		4	4		16	44	44
17'-0" (5.18 m)	4	4			4	16	44	44
18'-0" (5.48 m)	8					8	48	48


Table gives number of items needed

A 2'-0" high Xlife universal panel as the topmost panel requires only one Universal fixing bolt 5-12cm + Super-plate at each corner of the column.

with Xlife universal panels and Xlife standard panels

Certain cross-sections of column can be formed highly economically by combining Xlife universal panels and standard Xlife panels.

Possible cross-sections:



a ... up to 28" (71 cm), in 2" (5.1 cm) increments
Example: 16" x 24" (40.6 x 61 cm) column


A Frami S Xlife universal panel

B Frami S Xlife panel (max. 2'-0")

C Frami universal fixing bolt 5-12cm

D Super-plate 15.0

Materials schedule:




Formwork height (H)	Xlife universal panels (A)				Xlife panels (B)			
	9'-0"	6'-0"	4'-0"	3'-0"	9'-0"	6'-0"	4'-0"	3'-0"
3'-0" (0.91 m)				2				2
4'-0" (1.22 m)			2				2	
6'-0" (1.83 m)		2				2		
7'-0" (2.13 m)			2	2			2	2
8'-0" (2.44 m)			4				4	
9'-0" (2.74 m)	2				2			
10'-0" (3.05 m)		2	2			2	2	
11'-0" (3.35 m)			4	2			4	2
12'-0" (3.65 m)	2			2	2			2
13'-0" (3.96 m)	2		2		2		2	
14'-0" (4.26 m)		2	4			2	4	
15'-0" (4.57 m)	2	2			2	2		
16'-0" (4.87 m)	2		2	2	2		2	2
17'-0" (5.18 m)	2		4		2		4	
18'-0" (5.48 m)	4				4			

Formwork height (H)	Frami clamp (C)	Frami universal fixing bolt 5-12cm (D)	Super-plate 15.0 (E)
3'-0" (0.91 m)		8	8
4'-0" (1.22 m)		12	12
6'-0" (1.83 m)		16	16
7'-0" (2.13 m)	8	20	20
8'-0" (2.44 m)	8	24	24
9'-0" (2.74 m)		24	24
10'-0" (3.05 m)	8	28	28
11'-0" (3.35 m)	16	32	32
12'-0" (3.65 m)	8	32	32
13'-0" (3.96 m)	8	36	36
14'-0" (4.26 m)	16	40	40
15'-0" (4.57 m)	8	40	40
16'-0" (4.87 m)	16	44	44
17'-0" (5.18 m)	16	48	48
18'-0" (5.48 m)	8	48	48

Table gives number of items needed

with outside corners and Xlife panels

Column dimensions of **6" (15.2 cm)**, **12" (30.5 cm)**, **18" (45.7 cm)** and **24" (61 cm)** can also be formed with **outside corners** and **Xlife panels**.




Example: 18" x 18" (45.7 x 45.7 cm) column


- A** Frami S Xlife panel (max. 2'-0")
- B** Frami S outside corner
- C** Frami clamp
- D** Frami S frontal triangular ledge 3/4"

Materials schedule:

up to 18" (45.7 cm)



up to 24" (61 cm)



Example: Outside corners 9'-0" with Xlife panels 1'-6"x9'-0"

Example: Outside corners 9'-0" with Xlife panels 2'-0"x9'-0" and extra Frami clips



NOTICE


For 24" (61 cm) wide columns, 4 Frami clips for every 9'-0" (2.74 m) of column height are also required in the Frami outside corner.

Panel height (H)	Xlife panels (A)				Outside corners (B)				Frami clamps (C)
	9'-0"	6'-0"	4'-0"	3'-0"	9'-0"	6'-0"	4'-0"	3'-0"	
3'-0"				4				4	16
4'-0"			4				4		24
6'-0"		4				4			32
9'-0"	4				4				48

Table gives number of items needed


with outside corners and Xlife universal panels

Column dimensions of **36" (91.5 cm)** can also be formed with **outside corners** and **Xlife universal panels**.



- A** Frami S Xlife universal panel
- B** Frami S outside corner
- C** Frami clamp
- D** Frami clip
- E** Frami S frontal triangular ledge 3/4"

Materials schedule:




Example: Outside corners 9'-0" with Xlife universal panels 3'-0"x9'-0"

Panel height (H)	Xlife universal panels (A)				Outside corners (B)				Frami clamps (C)	Frami clips (D)
	9'-0"	6'-0"	4'-0"	3'-0"	9'-0"	6'-0"	4'-0"	3'-0"		
3'-0"				4				4	16	16
4'-0"			4				4		24	16
6'-0"		4				4			32	24
9'-0"	4				4				48	32

Table gives number of items needed

with column hinge and Xlife panels


The Frami S column hinge makes for **easy opening and closing** of the column formwork. This does away with time-consuming assembly and dismantling work. In conjunction with Xlife panels and outside corners, the column hinges make it possible to form column dimensions of **6" (15.2 cm)**, **12" (30.5 cm)**, **18" (45.7 cm)** and **24" (61 cm)**.



Example: 18" x 18" (45.7 x 45.7 cm) column

- A** Frami S Xlife panel (max. 2'-0")
- B** Frami S outside corner
- C** Frami clamp
- D** Frami S column hinge
- E** Hexagon bolt DIN 933 M18x50 8.8 galv.+
Hexagon nut DIN 934 M18 8 galv.

Materials schedule:



NOTICE


- For 24" (61 cm) wide columns, 4 Frami clips for every 9'-0" (2.74 m) of column height are also required in the Frami outside corner.
- For 24" (61 cm) wide columns, 4 extra screws are also required in the Frami S column hinge for every 9'-0" (2.74 m) of column height.

Panel height (H)	Xlife panels (A)				Outside corners (B)			
	9'-0"	6'-0"	4'-0"	3'-0"	9'-0"	6'-0"	4'-0"	3'-0"
3'-0"				4				3
4'-0"			4				3	
6'-0"		4				3		
9'-0"	4				3			

Panel height (H)	Column hinge (D)			Hexagon bolt + hexagon nut (E)	Frami clamp (C)
	6'-0"	4'-0"	3'-0"		
3'-0"			1	6	12
4'-0"		1		8	18
6'-0"	1			12	24
9'-0"	1		1	18	36

Table gives number of items needed

Pouring platform with Frami bracket 60



- A** Frami bracket 60 (floor and railing planking provided at site)
- B** Handrail clamp S (railing planking provided at site)
- C** Board for screwing the floor planking onto


Note:

Where the two floor planking units meet, a board must be screwed onto the underside.

For more information on constructing pouring platforms, see 'Pouring-platforms with single brackets'.

Lifting by crane

Frami lifting hook



Follow the additional directions in the Operating Instructions!

Position of the lifting hooks



Before repositioning the formwork, take into account the centre-of-gravity position of the formwork half.

- Choose a suitable position for the lifting hooks.
- Adjust the lifting chain by shortening one of the lengths of chain.

Securing the lifting hooks against slipping sideways

Use bolts to secure the lifting hooks so that they cannot slide from side to side:

- 1) Insert hexagon bolts M18 into the cross boreholes of the frame profile and secure them with hexagon nuts M18.




a ... 152 mm (6")

C Hexagon bolt DIN 933 M18x50 8x8 galv.

D Hexagon nut DIN 934 M18 8 galv.

The position of the pairs of bolts depends on the center-of-gravity position.

- 2) Place the lifting hooks on the frame profile, between the two bolts.



β ... max. 15°

C Hexagon bolt DIN 933 M18x50 8x8 galv.


D Hexagon nut DIN 934 M18 8 galv.

Footings and grade beam formwork

The Frami panels can also be used for footings and grade beams.

This is particularly advantageous where it is intended to continue forming (i.e. the walls) using the same panels. Footings and grade beams can quickly be formed with any of the Frami panels, with the panels either upright

or horizontal. Frami clamps, and a blow with the hammer, are all it takes to join the panels. Length adjustments and corners are solved just as simply as in 'normal' walls. A range of practical accessories makes the work very much easier.




98032-352-01

Tying horizontal Xlife panels


Top tie

with Frami S top yokes and Frami clips



98032-372-01

- Tie-rod is held above panel (not in the concrete)



A Frami S top yoke 4"-32"

B Frami clip

Frami S top yoke 4"-32":

Permitted capacity: 1.12 kip (5.0 kN)

Frami clip:

Permitted tensile force: 2.245 kip (10.0 kN)

Permitted shear force: 1.12 kip (5.0 kN)

Permitted moment: 0.15 kip-ft (0.20 kNm)

Number of ties needed:


Xlife panel (horizontal)	Number of ties
3'-0"	1 *)
4'-0"	1 *)
6'-0"	2
9'-0"	2

*) Two ties are needed in the first panel, and two in the last panel.


Possible wall thicknesses:

Wall thicknesses	Grid	Number of Frami S top yokes 4"-32"
4" - 32" (10 - 81 cm)	2" (5.1 cm)	1 per tie
33" - 47" (83.5 - 119 cm)	1" (2.5 cm)	2 per tie *)
47 1/2" - 64 1/2" (120.2 - 163.2 cm)	1" (2.5 cm)	2 per tie *)

*) join these top yokes with 2 Frami clips.



Special cases for wall thicknesses of 33" and 34":




Wall thickness	How to fix the top yokes
33"	Bolt to both sides
34"	1 bolt, 1 Frami clip

A Frami S top yoke 4"-32"


C Speed bolt 5/8 x 1 3/4" (M16x45)

Bottom tie

with Doka perforated tape and Frami foundation clamps



- Tie is held beneath the panel
- Wall thicknesses: in 2" (5.1 cm) increments



C Frami foundation clamp

D Doka perforated tape (expendable anchoring component)

Frami foundation clamp:


Permitted capacity: 1.795 kip (8.0 kN)

Required numbers of Doka perforated tapes:

Formwork height	Xlife panel (horizontal)	Number of Doka perforated tapes	Position
Up to 2'-6" (76 cm)	3'-0"	1 *)	Right next to the panel joint (1', 30 cm)
	4'-0"	2	
	6'-0"	2	Each 2'-0" (61 cm) from the panel joint
	9'-0"	2	
Up to 3'-0" (91 cm)	3'-0"	1 *)	Right next to the panel joint (1', 30 cm))
	4'-0"	2	
	6'-0"	2	2 tapes right next to the panel joint and 1 tape 4'-0" (122 cm) from the panel joint
	9'-0"	3	

*) Two Doka perforated tapes are needed in the first panel, and two in the last panel.


Doka perforated tape



Z ... Length of tape cut off roll: Wall thickness + 15 3/4" (40 cm)

	a	b	c
Doka perforated tape S 2" 25m	3/4"	2"	2"

with Frami bracing clips and Doka Express anchors 16x125mm




- The form tie is not in the concrete



NOTICE

Use Frami bracing clips only on foundation slabs and concrete floor-slabs.



E Frami bracing clip

F Doka express anchor 16x125mm + Doka coil 16mm

Frami bracing clip with Express anchor:

Permitted capacity in B10 concrete: 3.6 kip (16 kN)

Permitted capacity in B20 concrete: 4.6 kip (20 kN)

Required concrete thickness: min. 8" (20 cm)

Required distance from edge: min. 6" (15 cm)



Required numbers of Frami bracing clips:

Concrete grade of the foundation slab	Formwork height	Xlife panel (horizontal)	Numbers of Frami bracing clips	Position
B10	up to 2'-6" (76 cm)	3'-0"	1 *)	Right next to the panel joint
		4'-0"		
		6'-0"	2	
	up to 3'-0" (91 cm)	3'-0"	1 *)	Right next to the panel joint
		4'-0"		
		6'-0"	2	
B20	up to 3'-0" (91 cm)	9'-0"	2	Each 2'-0" (61 cm) from the panel joint
		3'-0"	1 *)	Right next to the panel joint
		4'-0"		
		6'-0"	2	Each 2'-0" (61 cm) from the panel joint


*) Two Frami bracing clips are needed in the first panel, and two in the last panel.

Practical example


Xlife panel 3'-0"x3'-0"



Xlife panel 2'-0"x9'-0"




Xlife panel 3'-0"x9'-0"



with Frami bracing clips and Doka Express anchors 16x125mm


Xlife panel 3'-0"x9'-0"



Tying upright Xlife panels

Top tie

with Frami S top yokes and Frami clips




Number of ties needed:


Xlife panel (upright)	Number of ties	Position
3'-0"	1 *)	Right next to the panel joint
4'-0"		

*) Two ties are needed in the first panel, and two in the last panel.
For more information, see 'Tying horizontal Xlife panels'.

with Frami tie-holder bracket and Taper tie 3/4" to 1" & 5/8" [15.0] ends



- Tie-rod is held above panel (not in the concrete)





- A Frami tie-holder bracket
- B Taper tie 3/4" to 1" & 5/8" [15.0] ends
- C Super-plate 15.0
- D Wooden spacer

Required numbers of Frami tie-holder brackets:

Xlife panel (upright)	Number and position of Frami tie-holder brackets
3'-0"	Over every panel joint
4'-0"	

Bottom tie

with Taper tie 3/4" to 1" & 5/8" [15.0] ends




A Super-plate 15.0

B Taper tie 3/4" to 1" & 5/8" [15.0] ends

Required number of form-ties:

Xlife panel (upright)	Number and position of ties
3'-0"	At every panel joint
4'-0"	

with Doka perforated tape and Frami foundation clamps



Max. pour-heights:


Panel width	Max. pour height
3'-0"	3'-0" (90 cm)
2'-6"	3'-6" (106 cm)
2'-0"	4'-0" (122 cm)

Required numbers of Doka perforated tapes:

Xlife panel (upright)	Number and position of Doka perforated tapes
3'-0"	Over every panel joint
4'-0"	

For more information, see 'Tying horizontal Xlife panels'.

with Frami bracing clips and Doka Express anchors 16x125mm



98032-376-01



NOTICE

Only use Frami bracing clips on foundation slabs and concrete floor-slabs.

Max. pour-heights:

Concrete grade of the foundation slab	Panel width	Max. pour height
B10	3'-0"	3'-2" (96 cm)
	2'-6"	3'-6" (106 cm)
	2'-0"	4'-0" (122 cm)
B20	3'-0"	3'-6" (106 cm)
	2'-6"	4'-0" (122 cm)

Required numbers of Frami bracing clips:

Xlife panel (upright)	Number and position of Frami bracing clips
3'-0"	Over every panel joint
4'-0"	


For more information, see 'Tying horizontal Xlife panels'.

Tying horizontal Xlife universal panels


With Xlife universal panels, it is possible to tie the panels above a joint-sealing tape.

Note:


The max. tying height is 1'-0" (30 cm) – do not place the tie higher than this!




Practical example




Xlife universal panel 3'-0"x4'-0"



Xlife universal panel 3'-0"x6'-0"



Xlife universal panel 3'-0"x9'-0"



a ... max. tying height = 1'-0" (30 cm)

b ... 3'-0" (91 cm)


A Taper tie 3/4" to 1" & 5/8" [15.0] ends

B Frami S top yoke

E Joint-sealing tape

Tying inside the panel:

with Taper tie 3/4" to 1" & 5/8" [15.0] ends



A Super-plate 15.0


B Taper tie 3/4" to 1" & 5/8" [15.0] ends

Required number of form-ties:

Xlife universal panel (horizontal)	Number of ties
3'-0"	2
4'-0"	2
6'-0"	3
9'-0"	3

Pressure bracing at top

with Frami S top yokes and Frami clips



A Frami S top yoke 4"-32"

B Frami clip

Required numbers of pressure braces:


Xlife universal panel (horizontal)	Number of pressure braces
3'-0"	1 *)
4'-0"	1 *)
6'-0"	2
9'-0"	2

*) Two pressure braces are needed in the first panel, and two in the last panel.

Plumbing accessories

The Doka plumbing accessories are the safe, reliable way to set up and plumb the panels of the footing and grade beam formwork.


Plumbing the panels with the Plumbing strut 260



a ... min. 4'-9" (147 cm)

For more information, see the section headed 'Plumbing accessories'.

Plumbing the panels with the Adjusting strut 120



a ... min. 2'-7 1/2" - max. 4'-3" (82 - 131 cm)


A Adjusting strut 120 IB

B Strut head EB


C Strut shoe EB

Frost walls


1st casting section



2nd casting section



- A Frami S Xlife panel 4'-0"
- B Frami S Xlife panel 6'-0"
- C She-bolt 15.0mm x 16"
- D Super-plate 15.0
- E Euro rod 5/8" or Tie-rod 15.0mm
- F Wooden spacer
- G Plumbing strut 260 IB + Strut head EB




General remarks

Frami combined with . . .

Starting block D22

With the Starting block of the Dam formwork D22, you can also use the Frami panels for single-sided wall formwork.



A Starter-block unit D22

B Vertical waling D15 3.00m U120

C Spindle strut D15 3.00m

D Screw-on access bracket MF75

E Frami S Xlife panel




Follow the directions in the “Doka dam formwork” User Information!

Cleaning and care of your equipment

Concrete release agent

Doka-Trenn or Doka-OptiX is applied using the Doka sprayer for release agent.



Follow the directions in the 'Doka sprayer for release agent' Operating Instructions and on the containers of release agent.



NOTICE

- Before every pour:
 - Apply release agent to the formwork sheet and the end faces **extremely thinly, evenly and in a continuous layer**.
- Make sure there are no drips of release agent running down the formwork sheet.
- Applying too much release agent will spoil the concrete finish.




To determine the right dosage and to make sure that you are using the agent correctly, test it on less important parts of the structure first.

Cleaning



NOTICE

- Immediately after pouring:
 - Remove any blobs of concrete from the back-face of the formwork, using water (without any added sand).
- Immediately after stripping the formwork:
 - Clean the formwork with a high-pressure washer and a concrete scraper.
- Do not use any chemical cleaning agents!



Cleaning high formwork:

Provide a service tower at a suitable cleaning location.

- Wheel-around scaffold DF (formwork height up to 3,90 m)
- Working scaffold Modul (formwork height up to 6,70 m)
- Load-bearing tower Staxo 40 (formwork height over 6,70 m)

Cleaning equipment

High-pressure washer




NOTICE



- Appliance pressure rating: 200 to max. 300 bar
- Keep the water-jet the correct distance from the formwork, and move it at the right speed:
 - The higher the pressure, the further away from the formwork you must keep the jet and the faster you must move it across the surface.
- Do not aim the jet at one place for too long.
- Make only moderate use of the jet around the silicone sealing strip:
 - If the pressure is too high, this will damage the silicone sealing strip.
 - Do not aim the jet at one place for too long.

Concrete scraper

For removing concrete remnants, we recommend using a **Double scraper Xlife** and a paint scraper.



Functional description:




A Blade for dealing with heavy soiling

B Blade for dealing with slight soiling




NOTICE

Do not use pointed or sharp objects, wire brushes, abrasive disks or cup brushes.




Care

- Never strike the frame profiles with a hammer




- Do not use nails longer than 60 mm on the formwork.




A max. l=60 mm





- Do not throw panels down or allow them to drop.



























- Only stack panel gangs on top of one another with timber battens (**A**) between each layer.






















This prevents the formwork sheets from being damaged by the connector components.















	[lbs]	Article #		[lbs]	Article #
Frami S Xlife panel 3'-0"x9'-0"	181.0	588801500	Frami S Xlife universal panel 3'-0"x9'-0"	237.0	588807500
Frami S Xlife panel 2'-6"x9'-0"	159.0	588802500	Frami S Xlife universal panel 3'-0"x6'-0"	162.0	588808500
Frami S Xlife panel 2'-0"x9'-0"	145.0	588803500	Frami S Xlife universal panel 3'-0"x4'-0"	107.0	588860500
Frami S Xlife panel 1'-6"x9'-0"	116.0	588804500	Frami S Xlife universal panel 3'-0"x3'-0"	83.8	588809500
Frami S Xlife panel 1'-0"x9'-0"	95.5	588805500	Frami S Xlife universal panel 3'-0"x2'-0"	56.2	588810500
Frami S Xlife panel 6"x9'-0"	63.5	588806500	Frami S Xlife-Uni-Element		
Frami S Xlife panel 3'-0"x6'-0"	135.0	588811500			
Frami S Xlife panel 2'-6"x6'-0"	109.0	588812500			
Frami S Xlife panel 2'-0"x6'-0"	98.8	588813500			
Frami S Xlife panel 1'-6"x6'-0"	80.2	588814500			
Frami S Xlife panel 1'-0"x6'-0"	65.3	588815500			
Frami S Xlife panel 6"x6'-0"	41.9	588816500			
Frami S Xlife panel 3'-0"x4'-0"	94.8	588854500			
Frami S Xlife panel 2'-6"x4'-0"	75.8	588855500			
Frami S Xlife panel 2'-0"x4'-0"	66.1	588856500			
Frami S Xlife panel 1'-6"x4'-0"	67.5	588857500			
Frami S Xlife panel 1'-0"x4'-0"	46.1	588858500			
Frami S Xlife panel 6"x4'-0"	29.3	588859500			
Frami S Xlife panel 3'-0"x3'-0"	69.4	588821500			
Frami S Xlife panel 2'-6"x3'-0"	61.3	588822500			
Frami S Xlife panel 2'-0"x3'-0"	53.1	588823500			
Frami S Xlife panel 1'-6"x3'-0"	45.2	588824500			
Frami S Xlife panel 1'-0"x3'-0"	37.5	588825500			
Frami S Xlife panel 6"x3'-0"	21.8	588826500			
Frami S Xlife-Element					
	Galvanized				
					
Frami S Xlife inside corner 1'-0"x9'-0"	138.0	588817500			
Frami S Xlife inside corner 1'-0"x6'-0"	94.1	588818500			
Frami S Xlife inside corner 1'-0"x4'-0"	67.2	588861500			
Frami S Xlife inside corner 1'-0"x3'-0"	52.5	588819500			
Frami S Xlife-Innenecke					
	Galvanized				
					
Frami S Xlife panel 8'-0"x9'-0"	606.0	588896500			
Frami S Xlife-Element 8'-0"x9'-0"					
	Galvanized				
					
Frami S outside corner 9'-0"	54.0	588827000			
Frami S outside corner 6'-0"	35.5	588828000			
Frami S outside corner 4'-0"	24.3	588862000			
Frami S outside corner 3'-0"	17.4	588829000			
Frami S-Außenecke					
	Galvanized				
					














	[lbs]	Article #		[lbs]	Article #
Frami S Xlife pilaster panel 9'-0"	206.0	588838500	Frami S hinged outside corner A 9'-0"	64.4	588834000
Frami S Xlife pilaster panel 6'-0"	144.0	588839500	Frami S hinged outside corner A 6'-0"	42.5	588835000
Frami S Xlife pilaster panel 4'-0"	99.6	588865500	Frami S hinged outside corner A 4'-0"	28.7	588864000
Frami S Xlife pilaster panel 3'-0"	78.9	588840500	Frami S hinged outside corner A 3'-0"	21.6	588836000
Frami S Xlife-Stützenvorlageelement			Frami S-Scharnierecke A		
	Galvanized Length: 2' (61 cm) Width: 6" (15 cm)			Powder-coated, blue	
Frami S hinged inside corner I galv. 9'-0"	162.0	588831500	Frami S column hinge 6'-0"	31.5	588881000
Frami S hinged inside corner I galv. 6'-0"	109.0	588832500	Frami S column hinge 4'-0"	20.9	588882000
Frami S hinged inside corner I galv. 4'-0"	76.5	588863500	Frami S column hinge 3'-0"	15.7	588883000
Frami S hinged inside corner I galv. 3'-0"	60.4	588833500	Frami S-Stützengelenk		
Frami S-Scharnierecke I verzinkt					
	Galvanized				
Frami S hinged inside corner I 9'-0"	157.0	588831000	Hexagon bolt DIN 933 M18x50 8.8 galv.	0.33	588879000
Frami S hinged inside corner I 6'-0"	104.0	588832000	Sechskantschraube DIN 933 M18x50 8.8 verz.		
Frami S hinged inside corner I 4'-0"	75.0	588863000			
Frami S hinged inside corner I 3'-0"	60.0	588833000	Hexagon nut DIN 934 M18 8 galv.	0.11	588880000
Frami S-Scharnierecke I			Sechskanmutter DIN 934 M18 8 verz.		
	Powder-coated, blue				
Frami S hinged outside corner A galv. 9'-0"	65.0	588894000	Frami S steel filler 2"x9'-0"	22.5	588842000
Frami S hinged outside corner A galv. 6'-0"	43.0	588893000	Frami S steel filler 1 1/2"x9'-0"	20.9	588843000
Frami S hinged outside corner A galv. 4'-0"	28.9	588892000	Frami S steel filler 1"x9'-0"	15.4	588844000
Frami S hinged outside corner A galv. 3'-0"	20.9	588891000	Frami S steel filler 2"x6'-0"	15.0	588845000
Frami S-Scharnierecke A verzinkt			Frami S steel filler 1 1/2"x6'-0"	13.9	588846000
	Galvanized		Frami S steel filler 1"x6'-0"	9.3	588847000
			Frami S steel filler 2"x4'-0"	11.0	588866000
			Frami S steel filler 1 1/2"x4'-0"	10.4	588867000
			Frami S steel filler 1"x4'-0"	7.5	588868000
			Frami S steel filler 2"x3'-0"	9.7	588848000
			Frami S steel filler 1 1/2"x3'-0"	8.6	588849000
			Frami S steel filler 1"x3'-0"	6.4	588850000
			Frami S-Stahlausgleich		
				Powder-coated, blue	





	[lbs]	Article #		[lbs]	Article #
Frami S filler angle 3/4" 3'-0" Frami S filler angle 3/4" 4'-0" Frami S filler angle 3/4" 6'-0" Frami S filler angle 3/4" 9'-0" Frami S-Schalhautwinkel	7.3 10.1 15.4 23.1	588820000 588886000 588885000 588884000	 Galvanized		
Framax S bias cut corner I 2.70m Framax S bias cut corner I 1.35m Framax S Ausschalecke I	388.0 207.0	588527000 588528000	 Galvanized, powder-coated		
Framax stripping spindle I with ratchet Framax-Ausschalspindel I mit Ratsche	12.1	588653000	 Galvanized Height: 10" (24,8 cm)		
Frami tie-adapter for bias cut corner I Frami-Ankeradapter für Ausschalecke I	1.0	588492000	 Galvanized Height: 4 1/2" (11 cm)		
Frami profile adapter for bias cut corner I Frami-Profiladapter für Ausschalecke I	1.3	588491000	 Galvanized Height: 3 1/4" (8 cm)		
Framax quick acting clamp RU Framax-Schnellspanner RU	7.3	588153400	 Galvanized Length: 8" (20 cm)		
Frami panel shoe Frami-Elementschuh	2.9	588490000	 Galvanized Length: 6 1/2" (16 cm)		
Frami clamp Frami-Spanner	2.6	588433000	 Galvanized Length: 4 1/2" (11 cm)		
Frami adjustable clamp Frami-Ausgleichsspanner	7.9	588436000	 Galvanized Length: 1'-4" (40 cm)		
Frami universal waling 0.70m Frami universal waling 1.25m Frami-Klemmschiene	8.2 14.1	588439000 588440000	 Painted blue		
Framax S universal waling 0.90m Framax S universal waling 1.50m Framax S Klemmschiene	23.6 39.2	588519000 588520000	 Painted blue		
Multi-purpose waling WS10 Top50 6'-0" Mehrzweckriegel WS10 Top50 6'-0"	82.2	581603000	 Painted blue		
Frami wedge clamp Frami-Klemme	2.4	588441000	 Galvanized Length: 6 1/2" (16 cm)		
Frami universal fixing bolt 5-12cm Frami-Universalverbinder 5-12cm	0.95	588479000	 Galvanized Length: 9" (23 cm)		
Frami profile connector 5-18cm Frami-Profilverbinder 5-18cm	1.8	588493000	 Galvanized Length: 1'-1" (33 cm)		

	[lbs]	Article #		[lbs]	Article #
Frami stop-end waler tie 15-45cm Frami-Stirnabschaltzwinge 15-45cm  Galvanized Length: 2'-9" (85 cm)	19.4	588498000	Strut 340 Stütze 340 consisting of: (A) Plumbing strut 340 IB EF Galvanized Length: 6'-3" - 11'-3" (190,8 - 341,8 cm) (B) Prop shoe EB Galvanized Length: 8" (20 cm) Width: 4 1/2" (11 cm) Height: 4" (10 cm)	32.8	588247500
Frami lifting hook Frami-Umsetzbügel  Galvanized Width: 6" (15 cm) Height: 8" (21 cm) Follow the directions in the "Operating Instructions"!	16.5	588438000	Galvanized Delivery condition: separate parts 	4.0	588245500
Plumbing strut 260 IB Justierstütze 260 IB  Galvanized Length: 4'-10" - 8'-5" (146,8 - 256,7 cm)	28.2	588437500	Strut 540 Stütze 540 consisting of: (A) Plumbing strut 540 IB EF Galvanized Length: 10'-2" - 18' (310,5 - 549,2 cm) (B) Prop shoe EB Galvanized Length: 8" (20 cm) Width: 4 1/2" (11 cm) Height: 4" (10 cm)	63.7	588250500
Strut head EB Strebenkopf EB  Galvanized Width: 3 1/2" (9 cm) Height: 5 1/2" (14 cm)	3.1	588945000	Galvanized Delivery condition: separate parts 	4.0	588245500
Adjusting strut 120 IB Justierstrebe 120 IB  Galvanized Length: 2'-8" - 4'-3" (81,5 - 130,6 cm)	16.8	588248500			
Strut shoe EB Strebenschuh EB  Galvanized Width: 3 1/4" (8 cm) Height: 5" (13 cm)	2.1	588946000			

	[lbs]	Article #		[lbs]	Article #			
Pipe brace 12'-0"-21'-0"								
Rohrstütze 12'-0"-21'-0"								
consisting of:								
(A) Pipe brace 12'-0"-21'-0"	160.0	585091000						
(B) Speed bolt 3/4"x4"	0.64	585650000						
2 pcs.								
(C) Speed nut 3/4"	0.2	585652000						
2 pcs.								
(D) Pipe brace shoe S	6.4	585088500						
Painted yellow								
Galvanized								
Delivery condition: separate parts								
Pipe brace 22'-0"-40'-0"								
Rohrstütze 22'-0"-40'-0"								
consisting of:								
(A) Pipe brace 22'-0"-40'-0"	410.0	585092000						
(B) Speed bolt 3/4"x4"	0.64	585650000						
2 pcs.								
(C) Speed nut 3/4"	0.2	585652000						
2 pcs.								
(D) Pipe brace shoe S	6.4	585088500						
Painted yellow								
Galvanized								
Delivery condition: separate parts								
Frami S connection profile EB								
Frami S-Anschlussprofil EB								
			Painted blue					
			Height: 3'-5" (105 cm)					
Doka express anchor 16x125mm								
Doka-Expressanker 16x125mm								
			Galvanized					
			Length: 7" (18 cm)					
			Follow fitting instructions!					
Doka coil 16mm								
Doka-Coil 16mm								
			Galvanized					
			Diameter: 5/8" (1,6 cm)					
Frami bracket 60								
Frami-Konsole 60								
			Galvanized					
			Length: 3'-3" (98 cm)					
			Height: 5'-2" (157 cm)					
Handrail clamp S								
Schutzgeländerzwinge S								
			Galvanized					
			Height: 4' - 5'-7" (123 - 171 cm)					
Frami S frame hole plug								
Frami S-Ankerstopfen								
			Brown					
			Diameter: 1 1/8" (3 cm)					
Frami universal panel plug								
Frami-Abdeckstopfen								
			Yellow					
			Diameter: 3/4" (2 cm)					
Frami S bracing head EB								
Frami S-Stützenkopf EB								
			Galvanized					
			Width: 7 1/2" (19 cm)					
			Height: 7 1/2" (19 cm)					
Frami tie-holder bracket								
Frami-Ankerhaltewinkel								
			Galvanized					

	[lbs]	Article #		[lbs]	Article #
Frami S top yoke 4"-32" Frami S-Flachanker 4"-32"  Galvanized Length: 3'-2" (96 cm)	4.6	588889000	Frami transport hook Frami-Transporthaken  Galvanized Length: 7" (17,5 cm) Follow the directions in the "Operating Instructions"!	1.2	588494000
Frami S top yoke 4"-30" Frami S-Flachanker 4"-30"  Galvanized Length: 3'-3" (99 cm)	4.9	588837000	Dokamatic lifting strap 13.00m Dokamatic-Umsetzgurt 13,00m  Green Follow the directions in the "Operating Instructions"!	23.1	586231000
Frami clip Frami-Stecker  Galvanized Width: 1 1/8" (3 cm) Height: 4 1/2" (12 cm)	0.57	588434000	Taper tie system 3/4" to 1" 		
Frami bracing clip Frami-Bodenhalter  Galvanized Length: 5" (12,7 cm) Width: 2 3/4" (6,7 cm)	1.2	588495000	Taper tie 3/4"-1"x32" & 15.0mm ends Taper tie 3/4"-1"x38" & 15.0mm ends Taper tie 3/4"-1"x44" & 15.0mm ends Taper tie 3/4"-1"x52" & 15.0mm ends Kon. Ankerstab 3/4"-1" & 5/8" [15,0] End.	3.7 4.9 6.0 7.1	585820000 585821000 585822000 585823000
Frami foundation clamp Frami-Fundamentspanner  Galvanized Height: 3 1/2" (9 cm)	3.5	588452000	Super plate 15.0 Superplatte 15,0  Galvanized Height: 2 1/4" (6 cm) Diameter: 4 1/2" (12 cm) Width-across: 27 mm	2.4	581966000
Doka perforated tape S 2" 25m Doka-Lochband S 2" 25m 	37.5	588841000	She-bolt system 15.0 		
Frami S frontal triangular ledge 3/4" 9'-0" Frami S frontal triangular ledge 3/4" 6'-0" Frami S frontal triangular ledge 3/4" 4'-0" Frami S frontal triangular ledge 3/4" 3'-0" Frami S frontal triangular ledge 3/4" 2'-0" Frami S-Stirndreikantleiste 3/4"	3.7 2.4 1.7 1.2 0.82	588878000 588877000 588876000 588875000 588874000	Frami S she-bolt 15.0mm x 16" Frami S she-bolt 15.0mm x 24" Frami S-Ankerkopf 15,0mm 	1.9 2.6	588890000 588895000
Doka 4-part chain 3.20m Doka-Vierstrangkette 3,20m  Follow the directions in the "Operating Instructions"!	33.1	588620000	Super plate 15.0 Superplatte 15,0  Galvanized Height: 2 1/4" (6 cm) Diameter: 4 1/2" (12 cm) Width-across: 27 mm	2.4	581966000

	[lbs]	Article #		[lbs]	Article #
Tie rod system 15.0					
Tie rod 15.0mm galvanized 0.50m	1.6	581821000			
Tie rod 15.0mm galvanized 0.75m	2.4	581822000			
Tie rod 15.0mm galvanized 1.00m	3.1	581823000			
Tie rod 15.0mm galvanized 1.25m	4.0	581826000			
Tie rod 15.0mm galvanized 1.50m	4.9	581827000			
Tie rod 15.0mm galvanized 1.75m	5.5	581828000			
Tie rod 15.0mm galvanized 2.00m	6.4	581829000			
Tie rod 15.0mm galvanized 2.50m	7.9	581852000			
Tie rod 15.0mm galvanizedm	3.1	581824000			
Tie rod 15.0mm non-treated 0.50m	1.6	581870000			
Tie rod 15.0mm non-treated 0.75m	2.4	581871000			
Tie rod 15.0mm non-treated 1.00m	3.1	581874000			
Tie rod 15.0mm non-treated 1.25m	4.0	581886000			
Tie rod 15.0mm non-treated 1.50m	4.6	581876000			
Tie rod 15.0mm non-treated 1.75m	5.5	581887000			
Tie rod 15.0mm non-treated 2.00m	6.4	581875000			
Tie rod 15.0mm non-treated 2.50m	7.9	581877000			
Tie rod 15.0mm non-treated 3.00m	9.5	581878000			
Tie rod 15.0mm non-treated 3.50m	11.0	581888000			
Tie rod 15.0mm non-treated 4.00m	12.6	581879000			
Tie rod 15.0mm non-treated 5.00m	15.9	581880000			
Tie rod 15.0mm non-treated 6.00m	19.0	581881000			
Tie rod 15.0mm non-treated 7.50m	23.6	581882000			
Tie rod 15.0mm non-treatedm	3.1	581873000			
Ankerstab 15,0mm					
Super plate 15.0			2.4	581966000	
Superplatte 15,0					
	Galvanized				
	Height: 2 1/4" (6 cm)				
	Diameter: 4 1/2" (12 cm)				
	Width-across: 27 mm				
Wing nut 15.0			0.68	581961000	
Flügelmutter 15,0					
	Galvanized				
	Length: 4" (10 cm)				
	Height: 2" (5 cm)				
	Width-across: 27 mm				
Battered washer 12/18			3.3	581934000	
Winkelplatte 12/18					
	Galvanized				
	Special order only!				
Plastic tube 22mm 2.50m			0.99	581951000	
Kunststoffrohr 22mm 2,50m					
	PVC				
	Gray				
	Diameter: 1" (2,6 cm)				
Universal cone 22mm			0.011	581995000	
Universal-Konus 22mm					
	Gray				
	Diameter: 1 5/8" (4 cm)				
Plug 22mm			0.007	581953000	
Verschlussstopfen 22mm					
	PE				
	Gray				
Protective cap 15.0/20.0			0.066	581858000	
Schutzkappe 15,0/20,0					
	Yellow				
	Length: 2 1/4" (6 cm)				
	Diameter: 2 3/4" (6,7 cm)				
Tie-rod wrench 15.0/20.0			4.2	580594000	
Ankerstabschlüssel 15,0/20,0					
	Galvanized				
	Length: 1'-3" (37 cm)				
	Diameter: 3 1/4" (8 cm)				
Multi-trip packaging					
Doka multi-trip transport box 1.20x0.80m			154.0	583011000	
Doka-Mehrwegcontainer 1,20x0,80m					
	Galvanized				
	Height: 2'-7" (78 cm)				
Multi-trip transport box partition 0.80m			8.2	583018000	
Multi-trip transport box partition 1.20m					
Mehrwegcontainer Unterteilung					
	Steel parts galvanized				
	Timber parts varnished yellow				
Doka multi-trip transport box 1.20x0.80x0.41m			93.7	583009000	
Doka-Mehrwegcontainer 1,20x0,80x0,41m					
	Galvanized				
Doka accessory box			235.0	583010000	
Doka-Kleinteilebox					
	Timber parts varnished yellow				
	Steel parts galvanized				
	Length: 5'-1" (154 cm)				
	Width: 2'-9" (83 cm)				
	Height: 2'-6" (77 cm)				
	Special order only!				

	[lbs]	Article #		[lbs]	Article #
Bolt-on castor set B Anklemm-Radsatz B  Painted blue	74.1	586168000			
Doka skeleton transport box 1.70x0.80m Doka-Gitterbox 1,70x0,80m  Galvanized Height: 3'-8" (113 cm)	192.0	583012000			
Doka stacking pallet 1.55x0.85m Doka-Stapelpalette 1,55x0,85m  Galvanized Height: 2'-6" (77 cm)	90.4	586151000			
Doka stacking pallet 1.20x0.80m Doka-Stapelpalette 1,20x0,80m  Galvanized Height: 2'-6" (77 cm)	83.8	583016000			

Near to you, worldwide

Doka is one of the world leaders in developing, manufacturing and distributing formwork technology for use in all fields of the construction sector.

With more than 160 sales and logistics facilities in over 70 countries, the Doka Group has a highly efficient distribution network which ensures that equipment and

technical support are provided swiftly and professionally.

An enterprise forming part of the Umdasch Group, the Doka Group employs a worldwide workforce of more than 6000.

